

GH2S2-XL POWER UNIT

Part Number 701203512050



SPECIFICATIONS

Length:	23.0 in.	(584 mm)
Width (with one hose loop standard):	19.0 in.	(483 mm)
Height:	20.5 in.	(521 mm)
Weight (Ready-to-use)	114.0 lbs.	(51.7 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.2 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

DESIGN & OPERATIONAL FEATURES

- ★ Gasoline powered 5.5 horsepower, 4 cycle Honda® engine
- ★ Two high pressure, 2-stage pumping systems
- ★ Roll cage for protection and hose storage
- ★ Two tools can be connected and operated simultaneously
- ★ Two 2-way, 2-position selector valves
- ★ High pressure, two-stage pumping system
- ★ Non-toxic mineral base hydraulic fluid
- ★ Uses lead free gasoline



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226
Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com