

95 GPM Truck Foam System

STYLE 3096

Eight (8) quick change handle positions means less installation time. Improved pressure recovery provides greater versatility.

Features

- 8 quick change handle positions (easily changed after installation) means less installation time
- Specify inlet and outlet, 2", 2 1/2" NPT or 2" standard groove
- Improved pressure recovery provides greater versatility
- Choose 60, 95, or 125 gpm (230, 360, or 475 lpm)
- Performs well with both 75 and 100 psi rated nozzles. 75 psi (5 bar) nozzles allow longer hose lays and less reaction force.

Easily changed to water line use Each Truck System Includes:

- Rugged brass by-pass eductor
- Foam metering dial
- One 2" In-line Swing-Out valve - with built-in check valve
- Two 1" In-line Swing-Out valves
- One 1" check valve
- Four Style 1477 remote controls Note: Each truck system is for a single tank operation. A two tank system requires one (1) additional 1" Swing-Out Valve, 1" check valve and 1477 Remote Control.

Note: Each truck system is for a single tank operation. A two tank system requires one (1) additional 1" Swing-Out valve, 1" check valve and 1477 remote control.



Specifications

Style	3096
Warranty	
Weight	4 lbs (1.8 kg)
Type	Truck System
Material	Brass
Length	17 1/2" (445 mm)
Width	6 1/4" (159 mm)
Height	5 1/2" (140 mm)

95 GPM Truck Foam System

STYLE 3096

