

Akromatic 1250 Master Stream Nozzle

STYLE 5160

Designed for flows from 250 to 1250 gpm (950-4800 lpm) - At 80 psi (5.5 bar) operating pressure

-Built-in stream shaper

Features

Designed for flows from 250 to 1250 gpm (950-4800 lpm) - At 80 psi (5.5 bar) operating pressure

- Built-in stream shaper
- Pyrolite Nozzle
- Manual Pattern Control
- 250-1250 gpm (950-4800 lpm) flow; 250 - 1000 gpm (950-3800 lpm) optional flow
- 2 1/2" or 3 1/2" (65 or 89 mm) Inlet
- No Teeth
- 9 1/2" (241 mm) Long
- 12 lbs. (26.8 kg)

Applications/Solutions

- Fire OEMs



Specifications

Style	5160
Certification(s)	
Warranty	
Weight	12 lbs (5.4 kg)
Type	Master Stream
Material	Pyrolite
Brand	Akromatic
Swivel Inlet	2.5" or 3.5" (65 or 89 mm)
Length	9 1/2" (241 mm)
Flow (GPM)	250-1250 GPM
Flow (LPM)	950-4800 LPM

Akromatic 1250 Master Stream Nozzle

STYLE 5160

Akromatic 1250 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that provides a flow range of either 250 to 1000 gpm or 250 to 1250 gpm at 80 psi. The nozzle shall be constructed of durable, lightweight Pyrolite.