

Akromatic 2000 Electric Master Stream Nozzle

STYLE 5178

Akron Brass' Akromatic 2000 electric master stream nozzle is designed for flows from 500 to 2000 gpm (1900-7600 lpm) at an operating pressure of 80 psi (5.5 bar). This nozzle has a manual override and built-in stream shaper for ease of use. In addition, the Akromatic 2000 provides electric pattern control. To find out more about this master stream nozzle, contact an Akron Brass distributor today.

Features

Designed for flows from 500 to 2000 gpm (1900-7600 lpm) - at an operating pressure of 80 psi (5.5 bar)

- Manual override and built-in stream shaper
- Pyrolite
- Electric Pattern Control
- 500-2000 GPM (1900-7600 lpm) - 500-1500 GPM (1900 - 5700 lpm)

Optional Flow

- 3 1/2" (89mm) Inlet (NH or NPSH ONLY)
- No Teeth
- 12 or 24 Volt
- 9 1/2" (241 mm) Long
- 15 1/2 lbs (7.0 kg)



Specifications

Style	5178
Warranty	
Weight	15 1/2 lbs (7.0 kg)
Type	Master Stream
Material	Pyrolite
Brand	Akromatic
Length	9 1/2" (242 mm)
Width	10" (254 mm)
Height	8 7/8" (225 mm)

Akromatic 2000 Electric Master Stream Nozzle

STYLE 5178

Shown with 738 foam tube



Akromatic 2000 Electric Master Stream Nozzle

STYLE 5178

Akromatic 2000 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that maintains a consistent pressure throughout a flow range of either 500 to 1500 gpm or 500 to 2000 gpm at 80 psi.