

3 1/2" Generation II Swing-Out Valve (Body Only) with stainless ball



STYLE 8635

Non-locking heavy-duty valve with a stainless steel ball designed for the harsh realities of today's fire service when water contaminants challenge a valve's sealing capabilities. These apparatus valves feature the following:

- A single valve body that will accept a variety of actuators
- HydroMax™ technology: A patented ball geometry providing performance never seen before in swing-out valves

Actuator options:

- Manual Gear
- Electric Actuator
- R/S
- SZ

Actuator/handle and adapters not included in price.

Find a distributor near you if you're interested in these apparatus valves.

Features

- 3" waterway
- Non-Locking valve
- 316 stainless steel ball for longer valve life
- High quality brass body
- Improve sealing & increased gating ability
- Flow optimization reduces turbulence while in the gated position and requires lower operating forces
- No lubrication or regular maintenance required
- Simple two-seated design (no O-Rings to cut or lose during assembly or maintenance)
- Wide range of available adapters
- Designed and tested to exceed NFPA requirements
- Cast, machined and assembled at our facilities in Wooster, Ohio

Actuator options:

- Manual Gear
- Electric Actuator
- R/S
- SZ Adapters specified separately. See valve guide for complete list of available adapters.

Actuator/handle and adapters not included in price.

Specifications

Style	8635
Warranty	
Type	Apparatus
Material	Brass
Brand	Swing-Out
Length	4" (102 mm)
Internal Diameter	3" (78 mm)
Volts	12 V DC or 24 V DC

Applications/Solutions

- Fire OEMs

3 1/2" Generation II Swing-Out Valve (Body Only) with stainless ball

STYLE 8635

Manual Gear Actuator with Handwheel



Electric Actuator



Rack & Sector



SZ

