

Push-Pull Rams



Ram Accessory Kit
Part Number: 100004751800

Includes: 10" Ram extension,
Conical head
Claw attachment

SPECIFICATIONS

All AMKUS Rams

Maximum Push Force: 30,650 lbs. (136.3 kN)

Maximum Pull Force: 14,400 lbs. (64.1 kN)

Rated Input Pressure: 10,500 psi (724 bar)

AMK-20R Ram

Part Number 110200372000

Length Open: 21.0 in. (533 mm)

Length Closed: 15.4 in. (391 mm)

Width Overall: 12.8 in. (325 mm)

Depth: 10.0 in. (254 mm)

Weight_(Ready-to-use): 22.5 lbs. (10.2 kg)

AMK-40R Ram

Part Number 110200374000

Length Open: 40.0 in. (1016 mm)

Length Closed: 25.4 in. (645 mm)

Width Overall: 8.5 in. (216 mm)

Depth: 5.0 in. (127 mm)

Weight_(Ready-to-use): 33.0 lbs. (15.0 kg)

AMK-30R Ram

Part Number 110200373000

Length Open: 29.1 in. (739 mm)

Length Closed: 19.3 in. (490 mm)

Width Overall: 8.5 in. (216 mm)

Depth: 5.0 in. (127 mm)

Weight_(Ready-to-use): 27.0 lbs. (12.2 kg)

AMK-60R Ram

Part Number 110200376000

Length Open: 60.3 in. (1532 mm)

Length Closed: 35.5 in. (902 mm)

Width Overall: 8.5 in. (216 mm)

Depth: 5.0 in. (127 mm)

Weight_(Ready-to-use): 43.5 lbs. (19.7 kg)

DESIGN & OPERATIONAL FEATURES

- ★ Unique base design distributes load
- ★ Check valve design maintains load
- ★ Accessories available for increased capabilities
- ★ Push/Pull design allows use of standard AMKUS chain packages
- ★ Anodized for corrosion protection



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226

Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com