

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Adapters with additional locking device



1202

In the case of pneumatic conveying of powder and granulates in hoses with Storz couplings, an additional safeguard may be advisable, since strong vibration and the torsional stresses often present in hose lines might cause uncoupling during operation.

Nominal size	Lug spacing b (mm)	Inside dia. d (mm)	Female thread W	Face-to-face length L (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
25=D-DS	31	18	G 1	30	0,080	30252333		A
52=C	66	32	G 1¼	32	0,350	40408433		A
52=C	66	40	G 1½	32	0,350	40408333		A
52=C	66	44	G 2	40	0,350	40408033		A
65	81	45	G 2	59	0,550	60355533		A
65	81	58	G 2½	42	0,400	30308633		A
75=B	89	50	G 2	38	0,600	30262433		A
75=B	89	65	G 2½	42	0,630	30311533		A
75=B	89	65	G 3	74	0,620	60358133		A
100	115	89	G 4	47	0,820	60470837		A
110=A-DS	133	100	G 4	48	1,050	30314533		A
110=A-DS	133	100	G 4½	48	1,100	30311733		A
125	148	115	G 5	52	1,400	60470637		A
150-DS	160	130	G 6	96	1,780	30312033	3 lugs	A

Other couplings with locking device on request.

As per: 23.12.2011