

OPEN DESIGNS

4 and 5-Stage High Pressure Breathing Air Compressors

- › **Pressure**
up to 6000 psig
up to 414 bar
- › **Charging Rate**
35.9 to 145 scfm
1017 to 4106 l/min
- › **Power**
30 to 100 hp
22 to 75 kW



Open packages in horizontal or vertical configurations combine compressor and air purification system in a space saving design.

These compressors set the standard for larger capacity air requirements.

Open Designs

STANDARD SCOPE OF SUPPLY

- › BAUER breathing air purification system
- › BAUER PLC based controller with four line text display
- › NEMA 4 rated electrical enclosure with **UL**® listed control panel
- › Compressor low oil pressure and high temperature safety shutdowns
- › Emergency stop push button
- › Automatic condensate drain system with non-corrosive condensate reservoir and integrated float sensor. Automatic "Full" indication and compressor shutdown
- › Beltguard designed to meet OSHA guidelines
- › Soft start, isolation contactor, and circuit breaker providing instantaneous short circuit protection

AVAILABLE ACCESSORIES (factory installed)

- › Purification upgrade
- › CO monitor
- › SECURUS (K42V-E3 and K42-E3 only)
- › Interstage pressure gauges (locally mounted)
- › Air storage and Containment Fill Stations allow for customization to meet specific requirements

DIMENSIONS L x W x H inches (mm)

- › VERTICAL 42 x 78 x 74 (1067 x 1981 x 1880)
- › HORIZONTAL 114 x 82 x 66 (2896 x 2083 x 1676)

WEIGHT pounds (kg)

- › VERTICAL 1200 - 2800 (544 - 1270)
- › HORIZONTAL 1200 - 5000 (544 - 2268)

Technical Data

Model	Charging rate ¹⁾		Number of stages	Motor		FAD ²⁾	RPM	Purification system
	scfm	l/min		hp	kW			
5000 psig (345 bar)								
K42V-E3 ³⁾	42	1190	4	30	22	35	1300	P10
K42-E3 ³⁾	42	1190	4	30	22	35	1300	P10
K60V-E3	60	1700	4	40	30	50	1350	P12 SECURUS
K60-E3	60	1700	4	40	30	50	1350	P12 SECURUS
K80-E3	80.4	2277	4	60	45	67	1225	P14 SECURUS
K145-E3	145	4106	4	100	75	121	1125	P14 SECURUS
6000 psig (414 bar)								
H35V-E3	35.9	1017	4	30	22	29.8	1200	P10 SECURUS
H35-E3	35.9	1017	4	30	22	29.8	1200	P10 SECURUS
H80-E3	80.4	2277	5	60	45	67	1180	2x P10 SECURUS
H96-E3	96	2718	5	75	56	80	1100	2x P10 SECURUS

1) Based on recharging an 80 cubic foot tank from 500 to 3000 psig.

2) Compressor capacity referenced to standard inlet conditions.

3) SECURUS electronic moisture monitoring is not standard.

E3 = Three Phase Electric, 230/460 VAC/60 Hz. Other voltages available on request.

KV / HV = VERTICAL K / H = HORIZONTAL Dimensions and weight are approximate and are subject to change.

BAUER COMPRESSORS INC.

1328 Azalea Garden Rd. | Norfolk, VA 23502
 TEL. +1 (757) 855-6006
 FAX +1 (757) 857-1041
sls@bauercomp.com
www.bauercomp.com

BAUER MIAMI

10052 N.W. 53rd St. | Sunrise, FL 33351
 TEL. +1 (954) 746-2504
 FAX +1 (954) 746-2510
bflsales@bauercomp.com

BAUER SAN FRANCISCO

267 East Airway Blvd. | Livermore, CA 94551
 TEL. +1 (925) 449-7210
 FAX +1 (925) 449-7201
bauersf@bauercomp.com

OD

296.11.03.3SP

subject to alteration without notice or obligation