


Blazex CO₂ Fire Extinguisher BXC5 - Carbon Dioxide



CO₂



BXC5 Carbon Dioxide



Carbon Dioxide is tested on Class B (flammable liquid) fires and is used as a clean extinguishing agent on small fires.

PLEASE NOTE: For every 1kg of CO₂ in your premises you must ensure you have 5.5 metres of space.

Features

- Manufactured in Great Britain 
- Britannia offer a 10 year quality guarantee against material defects and workmanship
- Brass nickel plated valve with colour coded levers and screen
- Aluminum body
- Main approvals and certifications as below

EN3



TECHNICAL SPECIFICATION

Model	Capacity (Kg)	Fire Rating	Full Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Diameter (mm)	Height (mm)
BXC5	5	70B	11.6	-20° to + 60°C	50	16	3	152	660

SPECIFICATIONS

Operating Pressure @ 20°C	50bar
Test Pressure (PT)	250bar
Maximum Allowable Pressure (PS)	169.3bar
Cylinder Material	Chromium Molybdenum Alloy Steel
Operating Valve Material	Brass Material - EU grade CuZn40Pb2 - EU code CW617N
Horn Material	Polypropylene
Hose Material	PVC with Woven Polyester - Burst Pressure 450kg/cm2
Finish - Red RAL3000 UV Protection	Polyester Powder Paint - Thickness (85 microns avg)

COMPONENT PARTS

Item	Description	Part No.
A	Hose and Horn	BC030
B	Brass Tapered Valve	VLV0010
C	5kg Alloy CO ₂ Cylinder	CYL0060
D	Syphon Tube	TUBE0172
E	Transport Bracket & Strap	BRH0562
F	Safety Pin	BC055
-	Pull Tight Seal	BRH0175
-	Wall Bracket	BRH0550

