

Chubb FX Range – FX Alcohol Resistant Foam

Protecting your world



Model Product No.	CFAR6 7288/00
Height (mm)	600
Width (mm)	310
Shell Diameter (mm)	150
Capacity (litres)	6
Test Pressure (bar)	33
Working Pressure at 20°C	15
Weight Full (kg)	10.6
Weight Empty (kg)	4.6
Discharge Time at 20°C (secs)	30-40
Minimum Effective Discharge (%)	90
Temperature Range (°C)	+5 to +60
Fire Rating	13A : 113B

DO NOT ADD FREEZE PROTECTION

Class of fire



Fires involving freely burning materials. For example wood, paper, textiles and carbonaceous materials.



Fires involving alcohol based liquids. NOT COOKING OIL.

Method of use

Apply the spray over the area of the fire, moving it from side to side, until the fire is extinguished. In the case of flammable liquid fires, ensure that the foam flows gently over the top of the liquid until the fire is extinguished.

Call **0800 32 1666**

www.chubb.co.uk

© Chubb Fire & Security Limited 2016

This briefing is intended as general guidance and is not a substitute for detailed advice in specific circumstances. Although great care has been taken in the compilation and preparation of this edition to ensure accuracy, Chubb cannot in any circumstances accept responsibility for errors, omissions or advice given or for any losses arising from reliance upon information contained in this publication.

Chubb Fire & Security