

Chubb FX Range – CO₂ Gas Extinguishers

Protecting your world



Model Product No.	EC20C 7732/00	EC50C 7735/00
Height (mm)	531	820
Width (mm)	200	290
Cylinder Diameter (mm)	111	152
Capacity (kg)	2	5
Test Pressure (bar)	212	212
Working Pressure at 20°C	56	56
Weight Full without Horn Assembly (kg)	4.8	11.0
Weight Empty without Horn Assembly (kg)	2.8	6.0
Discharge Time at 20°C (secs)	6-16	15-40
Minimum Effective Discharge (%)	90	90
Temperature Range (°C)	-30 to +60	-30 to +60
Fire Rating	34B	70B

Class of fire



Fires involving flammable liquids. For example petrol and spirits. NOT ALCOHOL OR COOKING OIL.



Fires involving electrical equipment. For example photocopiers and computers.

Method of use

IT IS IMPERATIVE THAT THE POWER SUPPLY IS DISCONNECTED.

Aim the jet at the base of the flames and move continuously from side to side, across the area of the fire.

WARNING: CO₂ extinguishers can cause freeze burns if the nozzle or base comes into contact with skin, due to their low operating temperature. CO₂ has little cooling effect, so reignition can occur. Take extra care and reapply CO₂ if the fire reignites.

DANGER: CO₂ can asphyxiate in a confined space. After extinguishing the fire, leave the area and do not re-enter until it is safe to do so.

Call **0800 32 1666**

www.chubb.co.uk

© Chubb Fire & Security Limited 2016

This briefing is intended as general guidance and is not a substitute for detailed advice in specific circumstances. Although great care has been taken in the compilation and preparation of this edition to ensure accuracy, Chubb cannot in any circumstances accept responsibility for errors, omissions or advice given or for any losses arising from reliance upon information contained in this publication.

Chubb Fire & Security