

# Chubb FX Range – FX Spray Foam

Protecting your world



Model	FO6	FO9	CFO6	CF09
Product No.	7282/00	7283/00	7286/00	7287/00
Height (mm)	561	546	600	620
Width (mm)	300	365	310	290
Shell Diameter (mm)	150	190	150	190
Capacity (litres)	6	9	6	9
Test Pressure (bar)	33	33	33	33
Working Pressure at 20°C	15	15	15	15
Weight Full (kg)	9.5	13.8	10.6	15.7
Weight Empty (kg)	3.5	4.8	4.6	6.6
Discharge Time at 20°C (secs)	30-40	50-60	30-40	40-50
Minimum Effective Discharge (%)	90	90	90	90
Temperature Range (°C) foam only	+5 to +60	+5 to +60	+5 to +60	+5 to +60
Temperature Range (°C) with LFA	-10 to +60	-10 to +60	-10 to +60	-10 to +60
Fire Rating without LFA	21A : 183B	27A : 233B	21A : 183B	27A : 233B
Fire Rating with LFA	13A : 113B	13A : 183B	13A : 113B	13A : 183B

## Class of fire



Fires involving freely burning materials. For example wood, paper, textiles and carbonaceous materials.



Fires involving flammable liquids. For example petrol and spirits. NOT ALCOHOL OR COOKING OIL.

## Method of use

Apply the spray over the area of the fire, moving it from side to side, until the fire is extinguished. In the case of flammable liquid fires, ensure that the foam flows gently over the top of the liquid until the fire is extinguished.

Call **0800 32 1666**

[www.chubb.co.uk](http://www.chubb.co.uk)

© Chubb Fire & Security Limited 2016

This briefing is intended as general guidance and is not a substitute for detailed advice in specific circumstances. Although great care has been taken in the compilation and preparation of this edition to ensure accuracy, Chubb cannot in any circumstances accept responsibility for errors, omissions or advice given or for any losses arising from reliance upon information contained in this publication.

Chubb Fire & Security