

Chubb FX Range – FX Monnex

Protecting your world



Model Product No.	PO9M 7356/00
Height (mm)	614
Width (mm)	234
Shell Diameter (mm)	190
Capacity (kg)	9
Test Pressure (bar)	33
Working Pressure at 20°C	15
Weight Full (kg)	14.4
Weight Empty (kg)	5.4
Discharge Time at 20°C (secs)	20-25
Minimum Effective Discharge (%)	90
Temperature Range (°C)	-20 to +60
Fire Rating	233B

Class of fire



Fires involving flammable liquids. For example petrol and spirits. NOT ALCOHOL OR COOKING OIL.



Fires involving flammable gases. For example butane and propane.



Fires involving electrical equipment. For example photocopiers and computers.

Method of use

If the fire is caused by flammable gas, shut off the supply of fuel if possible. Aim the jet at the base of the flames. Drive the flames towards the far edge with a rapid sweeping motion until extinguished.

WARNING: Dry powder does not readily penetrate the inside of electrical equipment, as it has no cooling effect, is not as efficient as other agents, so reignition can occur. Take extra care and reapply dry powder if the fire reignites.

WARNING: When used inside buildings the powder is likely to restrict visibility.

Call **0800 32 1666**

www.chubb.co.uk

© Chubb Fire & Security Limited 2016

This briefing is intended as general guidance and is not a substitute for detailed advice in specific circumstances. Although great care has been taken in the compilation and preparation of this edition to ensure accuracy, Chubb cannot in any circumstances accept responsibility for errors, omissions or advice given or for any losses arising from reliance upon information contained in this publication.

Chubb Fire & Security