

# Chubb FX Range – FX Fry Fighter™

Protecting your world



Model Product No.	WCHEM6 7503/00
Height (mm)	662
Width (mm)	310
Shell Diameter (mm)	170
Capacity (litres)	6
Test Pressure (bar)	33
Working Pressure at 20°C	7
Weight Full (kg)	11.7
Weight Empty (kg)	4.4
Discharge Time at 20°C (secs)	30-40
Minimum Effective Discharge (%)	90
Temperature Range (°C)	-10 to +60
Fire Rating	13A 113B 75F

## Class of fire



Fires involving freely burning materials. For example wood, paper, textiles and carbonaceous materials.



Fires involving flammable liquids. For example petrol and spirits. NOT ALCOHOL.



Fires involving cooking oil and fat. For example olive oil, maize oil, lard and butter.

## Method of use

Apply gently over the surface of the fire keeping the nozzle at a distance of at least 1 metre. Always expel entire contents of the extinguisher even after flames have been extinguished.

Call **0800 32 1666**

[www.chubb.co.uk](http://www.chubb.co.uk)

© Chubb Fire & Security Limited 2016

This briefing is intended as general guidance and is not a substitute for detailed advice in specific circumstances. Although great care has been taken in the compilation and preparation of this edition to ensure accuracy, Chubb cannot in any circumstances accept responsibility for errors, omissions or advice given or for any losses arising from reliance upon information contained in this publication.

Chubb Fire & Security