

### Features

All bronze construction  
Corrosion resistant  
Straight stream to fog  
Inbuilt stream shaper  
Easy to maintain and clean

### Description

Uller nozzles are especially designed for Siv monitors or any other monitor with 2 1/2" water outlet. The nozzles are suitable for water and foam solutions. They are manufactured in rugged brass.

The discharge pattern is adjustable from fog to straight stream during operation. Flow rate can be changed in between use.

### Application

Ideal to use in connection with portable or fixed monitors due to their remarkable strengths and adjustable discharge pattern.

### Recommended foam concentrates

All foam concentrates can be used in combination with Uller nozzles

### Operation

The Uller nozzles are fitted with a 2 1/2" female thread, suitable for Siv monitor or any other monitor with 2 1/2" water outlet. After using foam solution, clean it with water. By turning the handles, the discharge pattern can be adjusted from straight stream to fog. Flow will remain the same regardless of spray pattern.

### Optional

- Other inlet thread
- Light alloy
- Self-inducting version



### Technical data

Flow rate	3800 lpm (others on request)
Nominal pressure	7 bar
Inlet	2 1/2" BSP FM (standard)
Material	Bronze
Length	229 mm
Weight	10 kg

Nozzle Pressure	Flow Setting	Actual Flow	Straight Stream Reach with water	
			Effective	Overall
BAR	LPM	LPM	Meters	
5	1900	1640	49	56
	2900	2400	59	65
	3800	3280	63	68
	4800	3280	63	68
7	1900	1900	58	63
	2900	2900	62	71
	3800	3800	69	80
	4800	4800	85	87
8.5	1900	2120	62	66
	2900	3180	66	76
	3800	4240	71	80
	4800	5296	88	91

Note: under an angle of 32 degr.