

Features

- Light alloy construction
- Corrosion protected
- Straight stream to fog
- Fixed flow rate
- Easy to maintain
- Pre-set to any induction ratio 1%, 3% or 6%

Description

These self-inducing water/foam nozzles, are especially designed for Siv monitors, but can also be mounted on any other monitor with 2½" water outlet and suitable for water and foam solutions. The discharge pattern is adjustable from fog to straight stream during operation. Foam ratio can be easily set, with interchangeable orifice plates, which are included. The nozzle comes with a 2,5 meter long industrial grade pick up-hose with quick coupling. The fixed flow nozzle is available with choice of 1325, 1900, or 2850 lpm at 7bar nozzle pressure.

Application

Ideal to use in connection with fixed monitors in industrial and marine applications.

Operation

The Uller nozzles are fitted with a 2½" female thread, suitable for monitor Siv or any other monitor with 2½" water outlet. Before use, After using foam solution, clean it with water. By turning the handles, the discharge pattern can be adjusted from straight stream to fog. Flow will remain the same regardless of spray pattern.



Technical data

Flow rate (fixed)	1325 / 1900 / 2850 lpm
Nominal pressure	7 bar
Inlet	2 ½" BSP FM (standard)
Max. operating pressure	14 bar
Material	Light alloy
Length	145 mm
Weight	6 kg

Flow@7 bar (LPM)	Throw(mtr) (AFFF 3%) Straight stream/ narrow fog	Water inlet	Foam inlet	Ratio (must specify)
1325	43/30	2 1/2"	1 1/2"	1, 3 or 6%
1900	53/30			
2850	58/30			

