



SUCTION INTAKE

Suction Intake

Elkhart Brass offers a special cast iron, butterfly valve with Elk-O-Lite® end caps for use as a suction intake in apparatus applications. The valve features:

- Aluminum/bronze disc
- Re-inforced EPDM seat (bi-directional)
- Two piece stainless steel stem
- Rated to 200 psi
- Finished in red urethane enamel with polished chrome hand-wheel and hard anodized end caps
- Gear operated version complies with NFPA 1901

APPARATUS VALVES

7-2



Gearbox can be rotated to assist with positioning without interference

Models		2850	2860
Waterway Size (Inches)		5"	6"
Operation Style	Gear	s	s
	Lever/Trigger	o	o
Weight (Lbs.)*		35.8	42.4
Available Adapters/End Caps	Type	Size	
	Rigid NPT Female	5"	•
		6"	•
	Rigid NHT Female	4.5"	•
		5"	•
		6"	•
	Storz F/S	4"	•
		5"	•
	NHT Swivel Female	4"	•
		4.5"	•
		5"	•
		6"	•
	NHT Male	4"	•
		4.5"	•
		5"	•
		6"	•

KEY s = standard o = option
 * Intakes only, excludes adapter options

HOW TO ORDER
• Select suction intake model (2850 or 2860).
• Select intake adapter from available options.
• Select discharge adapter from available options.
• Specify operation style (gear or lever/trigger).

ADDITIONAL INFORMATION
<p>OPTIONS</p> <ul style="list-style-type: none"> • NHT swivel Female adapters available with long handle or rocker lug. • Optional strainer available on male adapters. • Optional air bleeder valve on male adapters.
<p>THREADS</p> <ul style="list-style-type: none"> • Valve information is NHT unless otherwise specified. See index T-12 for alternative thread options.