

# THREE-POD VECTOR® MINI-LIGHTBARS

available in:



#### High Performance in a Mini-Lightbar

The latest evolution of the Federal Signal Three-Pod Vector<sup>®</sup> employs the breakthrough Solaris<sup>®</sup> LED reflector technology. The Three-Pod Vector SL delivers performance that typical linear mini-lightbars cannot. The patented V-Shape design provides critical off-axis lighting and the innovative Solaris LED technology provides maximum optical performance with minimal amp draw.

The Three-Pod Vector SL can be configured with Solaris LED modules or a combination of LED modules and Halogen lights. Please refer to the Specify All Options (SAO) form 3PVCSL-WKS for details. In addition, each Three-Pod Vector SL includes an Intelli-Flash flasher with eight flash patterns.

The Halogen Three-Pod Vector is also available with many of the same features. For specific details, see the SAO form 3PVC-WKS found on the fedsig.com website. Both the halogen and LED lightbars are provided with a permanent mounting kit. An optional magnetic mounting kit is available and must be ordered separately.

Federal Signal offers a five-year warranty on our LED modules and Halogen rotator mechanisms, however should service be required, the modular pod design allows for quick and easy maintenance.



#### > Features

- Patented V-shape design maximizes visibility at critical 45- and 90-degree angles on approach to intersections.
- Available in LED, Halogen, or combination LED/Halogen models.
- LED models feature Solaris LED technology.
- LEDs are available in amber, red, blue, white and green.
- Five-year warranty on LEDs and rotator mechanisms.
- Configurable custom models are available.
- Five-year warranty.



#### > How to Order

Choose one of the pre-select models or configure a model with the Specify All Options (SAO) forms provided at www.fedsig.com. For additional information on the Three-Pod Vector, call us at (800) 264-3578.

# **Pre-Select Models**

VC2112

All models include a permanent mount kit.

# **Three-Pod Vector (Halogen)**

| VC2101 | (1) 95 FPM in Pods 1& 3 and  |  |
|--------|------------------------------|--|
|        | (1) 175 FPM rotator in Pod 2 |  |

(1) 95 FPM in Pods 1& 3 and(1) traffic clearing light in Pod 2

### **Three-Pod Vector SL (LED)**

- 535300-00006 (3) Red Solaris LED modules in Pods 1 & 3 (2) Red Solaris LED modules in Pod 2 (Dome colors: Red/Red/Red)
- **535300-00014** (3) Red Solaris LED modules in Pods 1 & 3 (2) White Solaris LED modules in Pod 2 (Not NFPA Compliant) (Dome colors: Red/White/Red)
- **535300-00010** (3) Blue Solaris LED modules in Pods 1 & 3 (2) Blue Solaris LED modules in Pod 2 (Dome colors: Blue/Blue/Blue)
- **535300-00011** (3) Amber Solaris LED modules in Pods 1 & 3 (2) Amber Solaris LED modules in Pod 2 (Dome colors: Amber/Amber/Amber)


# **Optional Mounting Kit**

VC21MK Magnetic Mount Kit (ordered separately)

### SAO Forms

| 3PVC-WKS          | Halogen only                       |  |
|-------------------|------------------------------------|--|
| <b>3PVCSL-WKS</b> | Solaris LED or Solaris LED/Halogen |  |
|                   | combinations                       |  |

#### **Pre-Select Models**



|                         | Halogen           | LED                    |  |
|-------------------------|-------------------|------------------------|--|
| Physical Specification  |                   |                        |  |
| Current Draw            | 12.9A (per bar)   | 1.0A* (each reflector) |  |
| Physical Specifications |                   |                        |  |
| Length                  | 20.5 in (52.1 cm) |                        |  |
| Width                   | 19.0 in (48.3 cm) |                        |  |
| Height                  | 5.9 in (15.0 cm)  |                        |  |
| Ship Weight             |                   |                        |  |
|                         | 14.0 lbs (6.4 kg) | 18.0 lbs (8.2 kg)      |  |

Traffic Clearing Light

\*Amp draws stated at "steady-on" for both rotating and flashing lights. During normal operation, amp draw of flashing lights may be as much as 50% lower than stated amount.



FEDERAL SIGNAL

2645 Federal Signal Drive, University Park, IL 60484-0975 Tel.: (800) 264-3578 • Fax: (800) 682-8022 www.fedsig.com Vector, Solaris and Intelli-Flash are trademarks of Federal Signal Corporation.

3R

2W

(3) Red Solaris

(2) White Solaris