

Proreact[®] Fixed Activation Temperature End of Line Unit

A1398

The Fixed Activation Temperature End of Line Unit with test facility has also been certified to EN54-28:2016 and enables users to undertake hassle-free functional testing of the system. Users can verify normal conditions, trouble and alarm functions of a system by simulating a break in the cable or overheat condition.



FEATURES

- Designed for use in both indoor and outdoor installations
- Low smoke zero halogen material coating
- Wide coverage - up to 1,000 metres (3,280 ft) of Proreact Fixed Activation Temperature LHD cable per zone
- The Proreact Fixed Activation Temperature Sensor Control Unit can monitor up to two zones of Proreact Fixed Activation Temperature LHD cable
- Improved testing and maintenance functionality with the Proreact Fixed Activation Temperature End Of Line Unit
- Manufactured in the UK and short lead times ensuring quick delivery across Europe

APPROVALS

Worldwide approvals include EN54 to meet end user specifications certification. Visit our website for up-to-date approvals information.

MECHANICAL SPECIFICATION

Colour	White
Dimensions	155(h) x 145(w) x 60(d) mm (6"(h) x 5¾"(w) x 2¼"(d))
Rating	IP66 rated enclosure supplied with 2 IP67 rated cable glands
Weight	0.28 kg (½ lb)

ELECTRICAL SPECIFICATION

Inputs - end of line resistor 2x 5mm rising lamp

APPLICATIONS

Cable trays	Conveyor belts
Car parks	Mines
Cold storage	Oil and gas tank farms

