

AccuMax Fury

The new fully automatic AccuMax Fury proportioning system brings the most advanced technology and innovation to the industry's easiest to use "big water" foam system for industrial applications - all with pinpoint accuracy. Controls incorporate a large 3.5" (89 mm) LCD display, in wide contrast, for ease of reading in daytime/ bright sunlight and nighttime modes. The intuitive operator interface, customizable on-screen discharge name/number and discharge color matching rain guards make foam system operation simple to manage. The custom high-tactile feedback keypad makes push-button operation easier than ever. With an increased number of independent injectors, the AccuMax Fury system can easily supply foam proportioning to 15 individual discharges; each with the widest foam flow range in the industry. FRC TankVision Pro can also be integrated into the AccuMax Fury system to give you accurate tank information at each control.

Features/Benefits

- Large, impact resistant 3.5" (89mm) Sunlight Readable LCD screen for unmatched durability and high resolution graphics
- Full System Information Display- injection percentage, water flow, foam type, discharge ID/Name
- Simple push button operation – On/Off preset injection rates, increase/decrease
- Intuitive MENU feature for setup, calibration, and diagnostics
- Up to 15 Independent Injectors – Increased number of foam capable discharges
- Customizable visor color, screen ribbon, and text to match color and name of discharge
- TankVision Pro Integration- Real-time foam cell levels and tank warning
- Hydraulic Backup- a standalone hydraulic control with a watchdog system built-in for override during any disruption of the main hydraulic control system
- High Flow Range- Custom cut ball foam metering delivers the widest range of foam flow for every size injector-all with pinpoint accuracy
- Foam Supply Manager- Optional foam supply manager puts foam management operations in one unit. Simply chose on-board tank, off-load/tender foam, and flush the foam system all from one synchronized unit

Technical Specifications

- 12-30 VDC
- Foam pump sizes available (GPM)
 - 20 (75 lpm), 40 (150 lpm), 60 (225 lpm), 90 (340 lpm), 150 (565 lpm), 300 (1,130 lpm)
- Max operating pressure: 300 PSI (20 bar)
- Max number of injectors: 15
- Injector sizes available and foam flow ranges:
 - 0.5" - 1.0 – 26 GPM (3.7 – 100 lpm)
 - 1.0" - 1.8 – 60 GPM (6.8 – 225 lpm)
 - 1.5" – 5.0 – 150 GPM (19 – 565 lpm)
 - 2.0" – 20.0 – 300 GPM (75 – 1,130 lpm)
- Fury display:
 - 12-30 VDC
 - 3.5" (89 mm) LCD
 - Control Size: 3.75" (95 mm) wide X 5.75" (146 mm) tall

Planned Production Timing: November, 2019



AccuMAX Fury™