


Alpha 600	0.60kg BC Dry Powder	Fire Rating 21B
Beta 950	0.95kg BC Dry Powder	Fire Rating 34B



- BSI certified to BS6165 : 2002 and Kitemarked
- 3** marked. European Aerosol Directive 1975
- Manufacturer's 5 year warranty
- Easy low cost maintenance
- Suitable for B & C Fire classifications
- Safe for use on electrical equipment
- Aluminium lightweight body
- Factory Sealed - Stored pressure
- Controlled discharge & Easy to operate
- Durable plastic (Polypropylene) bracket (Alpha)
Coated metal spring clip (Beta)

Manufactured in the UK under ISO 9001:2000 Quality Management System

These 600g & 950g BC Powder Fire Extinguishers are designed for use on all types of motor vehicles, caravans and most areas around the home.

B and C class fires caused by: petrol (leaded or unleaded), diesel, oil, gas, paints, solvents, greases, and also fires involving electrical equipment, and gaseous fires.

Model	Alpha 600	Beta 950
Capacity	0.60 kg	0.95 kg
Total Weight	0.76 kg	1.10 kg
Total Height	281 mm	302 mm
Total Width	94 mm	96 mm
Working Temp.	-20 ⁰ to +60 ⁰ C	-20 ⁰ to +60 ⁰ C
Discharge Time	6 secs	9 secs
Discharge Range	2-3 m	2-3 m
Cyl. Test Pressure	18 bar	18 bar
Packing Specification		
Qty Per Carton	10	8
Carton Dimensions	35x29x17 cm	35x29x17 cm
Carton Volume	0.017 m ³	0.0173 m ³
Carton Weight	8.1 kg	9.2 kg
Qty Extinguishers per Pallet	880 (88 Cartons)	704 (88 Cartons)
Pallet Dimensions	120x100x152 cm	120x100x152 cm
Pallet Volume	1.83 m ³	1.83 m ³
Pallet Gross Weight	735 kg	832 kg



CERTIFIED TO BS EN3
LICENCE No:
KM541496



FM540779