






-  **Manufacturer's 5 year warranty**
-  **Stored pressure - Easy low cost maintenance**
-  **Powder coated, steel wire bracket**
-  **Suitable for A & B class fires**
-  **Brass valve - Easy to read pressure gauge**
-  **Controlled discharge**



This extinguisher is manufactured to meet PSV Regulations Road traffic Act amendment 1995 (to the former BS5423 : 1987) and as such can be used on passenger carrying vehicles to include taxis, mini buses and buses.

Refilling/Serviceing: Should be carried out annually to BS 5306 Part 3, 2009. After complete or partial use the extinguisher should be refilled to BS 6643 Part 1, 1985. Both refilling and servicing to be carried out by a competent person. Spares available on request.

Model	FBF1
Capacity	1 lt.
Total Weight	2.12 kg
Total Height	370 mm
Total Width (including bracket)	130 mm
Working Temp.	+5 <sup>o</sup> to +60 <sup>o</sup> C
Discharge Time	7 secs
Discharge Range	4 m
Operating Pressure	12 bar @ 20 <sup>o</sup> C
Minimum Burst Pressure	55 bar
Packing Specification	
Qty Per Carton	1
Carton Dimensions	38x11x11 cm
Carton Volume	0.0046 m <sup>3</sup>
Carton Weight	2.2 kg
Qty Extinguishers per Pallet	338 (338 Cartons)
Pallet Dimensions	120x100x150 cm
Pallet Volume	1.8 m <sup>3</sup>
Pallet Gross Weight	760 kg



FM540779