

funkwerk FT4

TETRA Industrial handset



Robust TETRA handset for safe voice communication in industrial applications

Highlights:

- ▶ High resolution 2.2" TFT colour display, 240 x 320 Pixel (QVGA), 262,000 colours
- ▶ Outdoor-compatible due to IP 65 protection (jet-proof and dust-tight)
- ▶ Robust, shock-resistant housing with all-around rubber bumper as additional shock absorber
- ▶ Extensive range of audio accessories, can be screwed to lateral 12-pin audio interface (IP 65)
- ▶ Illuminated and clearly differentiated keys for safe handling, even with gloves
- ▶ Two microphones, one loudspeaker and receiver capsule for clear and loud audio communication
- ▶ Big red emergency call button
- ▶ Individually assignable function keys
- ▶ Optical signalling for network login and alarm messaging status



funkwerk FT4

TETRA industrial handset

Features:

- ▶ TETRA radio set according to ETSI standard
- ▶ Red and clearly reachable emergency call button
- ▶ Emergency call in TMO and DMO mode
- ▶ Vibration alarm (option)
- ▶ Programming via USB interface
- ▶ 500 mW / 1 W audio amplifier at accessory interface
- ▶ PEI interface
- ▶ Three different memory card slots:
 - SIM card for E2E encryption
 - Mini SIM card for network provider data
 - MicroSD card for saving user-related settings and parameters
- ▶ Integrated GPS receiver (option)

Optional FT4 series accessories:

- ▶ IP 65-compatible audio accessories
- ▶ Desktop charger with second charging slot for additional battery charging
- ▶ 4-fold multi-charger
- ▶ Programming station with charging function for unit programming via USB, including PEI interface

Technical data of funkwerk FT4 TETRA Handset		
Dimensions:	145 x 60 x 36 mm	(without antenna)
Weight:	295 g	with 1500 mAh battery
	325 g	with 2700 mAh battery
Degree of protection:	IP 65, water and dust according to IEC 60529	
Temperature ranges:	Operation:	-20 ... +55 °C
	Charging:	0 ... +40 °C
	Storage (without battery):	-30 ... +75 °C
Power supply:	Lithium polymer battery, 3.7 V, 1500 mAh	
	Option: Lithium polymer battery, 3.7 V, 2700 mAh, including vibration function	
RF specifications:	Frequency range:	380-430 MHz 410-470 MHz (in preparation) other frequency ranges on request
	RF Channel bandwidth:	25 KHz
Duplex spacing:	10 MHz (380-470 MHz)	
RF transmit power:	1 Watt, performance class 4	
Receiver class:	A&B	
Transmit power regulation:	in 3 steps of 5 dB each	
Sensitivity (static/dynamic):	-112 dBm / -103 dBm	
Range extension (option):	3 dB gain antenna	
Operating modes:	GPS (option):	integrated GPS antenna
Display:	High-resolution 2.2" TFT colour display	
	Up to 262,000 colours with 240 x 320 pixels (QVGA)	
Keys / controls:	Operating concept for easy handling:	
	▶ Illuminated alphanumeric keypad	
	▶ Full and partial keypad blocking	
	▶ Operation even with gloves due to clearly differentiated keys	
	▶ 3 lateral freely assignable function keys	
	▶ Big and easily reachable emergency button with two-stage Security emergency call alarm	
	▶ 3 navigation and 2 selection keys for easy menu navigation	
▶ Two-level rotary button for volume and group selection		
Phone book for telephone and radio users		
Scan list function with 16 lists and 16 voice groups per list		
Voice services (TMO):	Group call, Late Entry, Individual call, Half / full duplex, Telephony, Full duplex, Emergency calls in the TETRA and in the public network (e.g. 911)	
Voice services (DMO):	Group call, Individual call, Emergency call to DMO group, Support for DMO gateway mode	
Messages:	Status messages	Definition of up to 32 status messages
	Short messages	Storage of up to 16 short messages (SDS)



Charger with additional charging slot for second battery



Robust, shock-resistant housing, illuminated keypad with good differentiation for use when wearing gloves

Funkwerk Security Communications GmbH
John-F.-Kennedy-Str. 43-53
D-38228 Salzgitter

Phone: +49-5341 - 22 35-0
Fax: +49-5341 - 22 35-709

www.funkwerk-sc.com
info@funkwerk-sc.com