

Fyr Flote

Portable Floating Pump



The Fyr Flote is a lightweight, portable centrifugal pump mounted on an unsinkable, high-strength polyethylene float with dual carrying handles and a splash suppression collar. A high-volume model (20FV-C8) and a high-pressure model (20FP-C8) meet most every pump need — in as little as four inches of water. Weighing just 49 pounds, the Fyr Flote stores easily in most truck compartments. It includes an automatic recoil starter, a spark arresting muffler, and an engine overspeed control switch.

Technical Specifications

Pump

Type: Centrifugal, bolted to engine.

Suction: Two inch, non-threaded, with easily removable oversized screen.

Discharge: One and half inch NST male.

Head: Lightweight, high strength, corrosion resistant aluminum alloy.

Volute: High strength aluminum alloy with machined waterways for maximum performance.

Impeller: Bronze enclosed type for maximum efficiency.

Clearance Rings: Patented floating bronze clearance ring for minimum clearance, to prevent rubbing, seizing, and alignment problems.

Pump Shaft: Engine's vertical shaft serves as pump shaft, protected against corrosion by a bronze sleeve.

Shaft Seal: Self-adjusting, self-lubricated using a special ceramic seat for wear and shock resistance.

Priming: Exclusive auto prime system works without a suction hose.

Engine

Make: U. S. Motor Power Inc.

Type: Single cylinder, two-cycle gasoline.

Horsepower: 8 HP at 7,000 RPM.

Cooling: Forced air.

Starting: Water-resistant, solid state ignition.

Air Filter: Wire mesh element protects against impurities.

Fuel Filter: 75 micron in-line fuel filter; a fuel strainer is built in to the fuel pump.

Options

Stowaway Accessory Package

100 feet x 1-1/2 inch hose, adjustable nozzle, tune-up kit, and one quart N.M.M.A (BIA) approved 2-cycle engine oil in canvas bag.

Dimensions

Length: 28.25 inches (718 mm)

Width: 20 inches (508 mm)

Height: 16 inches (406 mm)

Weight: 49 pounds (22 kg)


PORTABLE PUMPS



Hale Products, Inc. A Unit of IDEX Corp. 700 Spring Mill Avenue Conshohocken, PA 19428 USA
TEL: 610/825-6300 1-800/220-HALE FAX: 610/825-9615 www.haleproducts.com
Class 1 A Unit of IDEX Corp. 607 NW 27th Avenue Ocala FL 34475 USA
Tel: 352-629-5020 800-533-3569 Fax: 352-629-2902 www.class1.com

Fyr Flote

Portable Floating Pump



PORTABLE PUMPS

	High Volume 20 FV-C8		High Pressure 20FP-C8	
	95% Maximum BPH			
GPM (LPM)	PSI	BAR	PSI	BAR
10 (38)	125	8.6	170	11.7
50 (190)	95	6.6	90	6.2
140 (530)	25	1.7	—	—

Bulletin #695, Rev. 3 • Copyright 2004 Hale Products Inc.
 Note: Hale Products Inc. cannot assume responsibility for product failure resulting from improper maintenance or operation. Hale is responsible only to the limits stated in the product warranty. Product specifications contained in this material are subject to change without notice.

