

Standard Features

Horton 533

Type III Ford E-450

Chassis

Wheelbase and CA.....	158" WB, 100" CA
Engine.....	6.8 Liter Triton V10 Gasoline
GVW	14,500 lbs.
Wheels and Tires	(7) 225/75R16E
Wheel Covers	(4) Polished Stainless
Alternator	(1) 225 Amp
Batteries	(2) 750 CCA
Mirrors	Below Eye Level Telescopic With Power Glass
Seats.....	Cloth High Back Bucket
Driver and Passenger Air Bags.	Yes
Trim Level	18A Upgrade Package
Radio/CD	AM/FM/CD
Fuel Tank Capacity	55 Gallons

Body

Length and Width.....	163" x 96"
Headroom	72"
Number of Compartments.....	(5) Polished Diamond Plate
Body Skin Thickness125"
Body Skin Alloy	5052H34
Body Vertical Structure.....	2" X 2" Square Tube, .125" Wall
Compartment Thickness.....	.125" Diamond Plate
Cubic Foot Storage (total)	185.39
Exterior Compartments.....	81.79
Interior Compartments.....	103.60
Rear Step.....	Lift Up Style with Grip Strut Center
Fenders	Polished Stainless
ICC Lights	LED
Rub Rails	Polished Stainless with End Caps
Rear Door Hold Opens	Grabber Style, Chrome
Sound Control	Acoustic/Thermal Spray and Dampening Pad
Door Handles	TriMark Chrome Plated
Lock System.....	Power Locks on Access Doors
Structural Sub Flooring	2" X 2" Tubing with .250 Wall
Sub Floor Sheet Thickness.....	.090" Aluminum Plate
Mud Flaps	Front and Rear
Corner Guards.....	Diamond Plate

Interior Patient Area Cabinets

Cabinet Construction.....	Welded .063" Aluminum
Cabinet Configuration	ALS, BLS or Custom
Inside/Outside Storage	Right Front of Body
Cabinet Doors.....	Plexiglas or Solid
Sliding Cabinet Door Handles..	Full Height Extruded Aluminum

Solid Door Handles	Recessed Stainless Southco
Curb Side Cabinetry	Hinged Door Cabinet Above Squad Bench
Sharps/Waste.....	Yes

Patient Area Accessories

Sub Floor.....	.090" Aluminum Plate Plus .5" Composite
Flooring Material	Commercial Grade Loncoin with Antimicrobial Coating
Walls.....	High Density Aluminum Composite
Headliner	High Density Aluminum Composite
Interior Door Panels.....	Formica Covered .090" Aluminum
Windows	Extruded Aluminum Frames (All Doors and Over Bench)
Front Bulkhead.....	Hinged Walkthrough Door on Type 3, Window on Type 1
IV Provisions	(2) Recessed Cast Products with Rubber Stabilizer Arms
Grab Rails	(1) 6' 1.25" Diameter Stainless Steel With Agion Biohazard Coatings
Interior Door Grab Handles.....	(3) Angled 1.25" Diameter Stainless Steel, (1) On Each Access Door With Agion Biohazard Coatings
Side Door Hold Open	Gas Piston, Double Action Style
Squad Bench Hold Opens.....	Gas Piston Style
Squad Bench Cushion Latches..	Positive Recessed Paddle Handle Style
Work Counters.....	Stainless Steel
Cot Mount	FW 175-3 for BLS or FW 175-4 for ALS
Fire Protection.....	(2) 5 Lb. ABC Extinguishers
Attendant Seat.....	Box Style With Backrest
Seat Belts	All Seating Positions with Enclosed Retractors
Interior Door Reflectors	2" x 12" Red Scotchlite
Airbag Protection:.....	Side Impact Rollover Airbags for Attendant and CPR Seats

Electronic O₂ and Vacuum Systems

Oxygen System.....	Horton Electronically Controlled System
Oxygen Regulator.....	Victor 50 Lb. Preset
Bottle Pressure Indicator	Digital Readout On Patient and Driver Consoles And Analog Gauge in Exterior Oxygen Compartment
Line Pressure Indicator	Digital Readout On Patient and Driver Consoles

Vacuum system	Rico RS 4X
Vacuum Outlet.....	(1) NCG Style with Quick Connect
Pressure Warnings	Audible and Visual Warnings on Driver and Attendant Console for High and Low Pressure

O2 Bracket: Zico QRM-V with Wrench

Electronic System

System Design	Horton Intelliplex Solid State Multiplexed System
Switch Style	Magnetic Technology, Lighted Outline
Switch Ratings	50 Million Cycles
Switch Panel Style	Flush Mounted
Information Centers.....	Digital Message Centers on Front and Rear Consoles
Panel Backlighting System	Fiber Optic, Color Coded LED
Decontamination Capability	Sealed Panel, Crevice Free
System Features:	No Load Starting, Load Management, Diagnostics, Timer Circuits, Vehicle System Status, Oxygen Management, Trip Odometer, 24 Hour Clock, Low Voltage Warning, Discreet Door Open Warnings, Patient Status, Digital amperage and Voltage, Automatic Shutdown and Nearly Infinite customization Features

Patient Area Heating and A/C

Unit Style	ProAir 650 CFM
Capacity	32,000 BTU Cool, 65,000 BTU Heat
Static Intake.....	Roof Mounted
Power Exhaust.....	Roof Mounted
A/C Compressor.....	(2), Chassis OEM And Auxiliary
Condensor	Chassis OEM And Auxiliary
Control System.....	Automatic Climate Control

Interior/Exterior Illumination

Dome Light Style/Quantity	(7) Weldon Halogen Lights
Control System.....	Horton Infinite Intensity Adjustment
Attendant Area Illumination	3 Position Report Light
Step Well Light	Weldon with Chrome Bezel
Side Scene Lights	(2) 900 Series Whelen Halogen with Chrome Bezels
Rear Loading Lights	(2) Whelen 900 Series Halogen
Spotlight.....	(1) Optronics Hand Held in Cab
Tail Lights	Whelen 600 Series Halogen
Lower Marker/Turn Light.....	(2) Whelen 700 Series Halogen with Chrome Bezels
Compartment Lights	Full Height LED Strips
Compartment Light Activation..	Automatic Switch When Door Is Opened

Visual and Audible Warning Systems

Front Body Warning Lights.....	(2) Whelen 900 Series Halogen (Red)
Rear Body Warning Lights	(2) Whelen 900 Series Halogen (Red)
Side Body Warning Lights.....	(4) Whelen 900 Series Halogen (Red)
Grille Lights	(2) Whelen 700 Series LED (Red)
Intersection Lights	(2) Whelen 400 Series Halogen (Red)
Front KKK Light	(1) Whelen 700 Series Halogen (Clear)
Rear KKK Light	(1) Whelen 700 Series Halogen (Amber)
Siren	(1) SVP SS700 200 Watt
Speakers	(2) Cast SA 4319
Reverse Alarm	With Resetting "Disable" Feature
Standby Switching	Automatic with Programmable Priority

Radio Provisions

Antenna Cables	(1) RG58U
Radio Pull Wire.....	(1)
Console.....	Custom
Radio Power Feed	(1) Behind Driver Area

Electrical Power

12 Volt Power	3 Cigarette Style Outlets
110 Volt Power	2 Wall Mounted Duplex Receptacles
12 Volt Breaker Style	Mosfet Solid State
110 Volt Breaker Style	20 Amp GFI
Shoreline	20 Amp with Weatherproof Cover
Battery Charger:	45 Amp

Paint

Stripe Style.....	White With KKK Scotchlite Beltline (Any Color)
-------------------	--