


Please refer to the description of the Control Centre / Control to identify the manual call points that can be connected

### **RT 2**

- Manual call point to VdS 2592 for the connection to SHEVS Control Centres / Controls
- Orange design with VdS approval no. G 501005
- Inscription „RAUCHABZUG“ (smoke exhaust)
- Indicator Alarm 
- Terminals for cables up to 1mm<sup>2</sup>
- 0,9mm thin break glass to DIN 1249
- Environmental conditions: -10 to +55°C, 20 to 80% rel. humidity (non condensing)
- Lockable ABS housing, dimensions (WxHxD): 125 x 125 x 35mm, protection rating IP42
- Each unit comes with a key
- Also available with customised inscriptions (e.g. “smoke exhaust” or “CO<sub>2</sub> extinguisher”)

### **Standard versions**

#### **Series RT 2-K-\***



***(secondary alarm point)***

- RT 2-K-OR: Version in orange, VdS approved  
RT 2-K-BL: Version in blue  
RT 2-K-RT: Version in red  
RT 2-K-GR: Version in grey  
RT 2-K-GE: Version in yellow



#### **Series RT 2-K-\*-BS**

***(main alarm point)***


- Same as secondary alarm point, but additionally
- Indicators operation , and malfunction 
  - Internal button to reset the alarm

- RT 2-K-OR-BS: Version in orange, VdS approved  
RT 2-K-BL-BS: Version in blue  
RT 2-K-RT-BS: Version in red  
RT 2-K-GR-BS: Version in grey  
RT 2-K-GE-BS: Version in yellow



#### **Series RT 2-K-\*-BS-A**

***(main alarm point with indication of position)***

- Same as main alarm point, but additionally
- Indication of position OPEN 

- RT 2-K-OR-BS-A: Version in orange, VdS approved  
RT 2-K-BL-BS-A: Version in blue  
RT 2-K-RT-BS-A: Version in red  
RT 2-K-GR-BS-A: Version in grey  
RT 2-K-GE-BS-A: Version in yellow



### Aluminium versions

- Same as standard version, but aluminium housing with protection rating IP 43

#### Series RT 2-A-\*



**(secondary alarm point, aluminium - version)**

- RT 2-A-OR: Version in orange, VdS approved
- RT 2-A-BL: Version in blue
- RT 2-A-RT: Version in red
- RT 2-A-GR: Version in grey
- RT 2-A-GE: Version in yellow



#### Series RT 2-A-\*-BS

**(main alarm point)**


- Same as secondary alarm point, but additionally
- Indicators operation , and malfunction 
  - Internal button to reset the alarm

- RT 2-A-OR-BS: Version in orange, VdS approved
- RT 2-A-BL-BS: Version in blue
- RT 2-A-RT-BS: Version in red
- RT 2-A-GR-BS: Version in grey
- RT 2-A-GE-BS: Version in yellow



#### Series RT 2-A-\*-BS-A

**(main alarm point with indication of position)**

- Same as main alarm point, but additionally
- Indication of position OPEN 

- RT 2-A-OR-BS-A: Version in orange, VdS approved
- RT 2-A-BL-BS-A: Version in blue
- RT 2-A-RT-BS-A: Version in red
- RT 2-A-GR-BS-A: Version in grey
- RT 2-A-GE-BS-A: Version in yellow



### Options

#### **AA:**

- Internal mini-buzzer for indication of alarm and malfunction
- Internal button to reset the mini-buzzer
- Available for main alarm points only

#### **IP54:**

- Set for weather protection and sealing, increases protection rating to IP54
- For aluminium versions only

### **RT-230**

- Manual call point to DIN 14655
- Inscription „RAUCHABZUG“ (smoke exhaust)
- Internal lever to reset the alarm
- 0,9mm thin break glass to DIN 1249
- 1 change-over contact, contact load rating 230V~ / 1A
- For direct connection to 230V Systems (not suitable for 24V- SHEVS Control Centres)
- Terminals for cables up to 1,5mm<sup>2</sup>
- Environmental conditions: -10 to +55°C, 20 to 80% rel. humidity (non condensing)
- Lockable aluminium housing, dimensions (WxHxD): 125 x 125 x 35mm, protection rating IP43
- Each unit comes with a key
- Also available with customised inscriptions (e.g. “smoke exhaust” or “CO<sub>2</sub> extinguisher”)

### **Series RT-A-\*-230**

RT-A-OR-230: Version in orange

RT-A-BL-230: Version in blue

RT-A-RT-230: Version in red

RT-A-GR-230: Version in grey

RT-A-GE-230: Version in yellow



### **Option**

#### **IP54:**


- Set for weather protection and sealing, increases protection rating to IP54

### Accessories

#### RT-E

- Spare glass sheet, blank, for manual call points series **RT** and **RT 2**
- 0,9mm thin break glass to DIN 1249
- Dimensions: 80 x 80mm (WxH)
- 1 packing unit = 10 pieces

**RT-E:**



#### RT-S

- Spare key for manual call points series **RT** and **RT 2**

**RT-S-K:** Standard key



**RT-S-A:** Metal key

