



SIS TYPE 30 / 600 AND AUS TYPE 30 / 1100 FT

Approved for storage of flammable liquids at the workplace as per EN 14470-1 (type 30) and TRbF 20 - L

- ◆ Whole construction tested and approved by an authorized materials testing institute as per EN 14470-1 (type 30) with a fire resistance >30 minutes
- ◆ Body made from B1 material RAL 7035 - light grey, door(s) either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ◆ Height-adjustable shelves at intervals of 32 mm
- ◆ Automatic thermal closing mechanism if fire occurs
 - Door after temperature increase to $\leq 50^{\circ}\text{C}$ and
 - Inlet and outlet channels after temperature increase to 70°C ($\pm 10^{\circ}\text{C}$)
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRbF 20-L (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with BGR 132 (avoidance of sources of ignition)
- ◆ Markings according to EN 14470-1 / TRbF 20, Annex L / ISO 3864
- ◆ Leveling feet for installing cabinet horizontally
- ◆ Door with cylinder lock
- ◆ Door hinged right as standard



Extraction fans please see page 140!

With inner fittings:

SIS Type 30 / 600 / SiS Type 30 / 600-1300

- ◆ 1 x base sump tray (sump capacity 23 liters)
- ◆ 1 x perforated base tray cover as 1st storing level
- ◆ 3 x shelves (SIS Type 30 / 600-1300: 2 x shelves)
- ◆ With automatic thermal closing mechanism



Socle incl., with removable panel



Safe compartment, SF Type 30/600, Dimensions W x D x H (mm) = 480 x 518 x 422,5; Art. No. B80-2660-A



SIS Type 30 / 600, Art. No. B80-2603-A, door RAL 1007 - daffodil yellow, incl. 3 shelves, base sump tray and perforated cover plate



SIS Type 30 / 600-1300, Art. No. B80-2608-A, door RAL 1007 - daffodil yellow, incl. 2 shelves, base sump tray and perforated cover plate

AUS Type 30 / 1100 FT, Art. No. B80-2602-A, incl. socle, Art. No. B80-2869-A

With inner fittings:

AUS Type 30 / 1100 FT

- ◆ 1 x base sump tray (sump capacity 26 liters)
- ◆ 1 x perforated base tray cover as 1st storing level
- ◆ With automatic thermal closing mechanism

Model		SiS Type 30 / 600	SiS Type 30 / 600-1300	AUS Type 30 / 1100 FT
External dimensions W x D x H (mm)		595 x 595 x 1935	595 x 595 x 1315	1100 x 570 x 600
Internal dimensions W x D x H (mm)		480 x 519 x 1660	480 x 519 x 1108	986 x 494 x 425
Door(s)		1 (hinged right)	1 (hinged right)	2
Weight (kg)		175	121	110
Outer body: RAL 7035 - light grey	Material inner fittings			
Art. No., door(s): RAL 7035 - light grey	sheet steel	B80-2601-A	B80-2607-A	B80-2602-A
Art. No., door(s): RAL 1007 - daffodil yellow	sheet steel	B80-2603-A	B80-2608-A	B80-2609-A

Accessories	Material	Article No.	Article No.	Article No.
Shelf	sheet steel	B80-2611-A	B80-2611-A	-
Socle height 35 mm	B1	-	-	B80-2869-A
Safe compartment	B1	B80-2660-A	B80-2660-A	-