

TRG 700 / TRG 1050 / TRG 1400

For the storage of pressurized gas cylinders as per TRG 280 indoors and outdoors

- Outer body made from galvanized sheet steel, powder-coated in RAL 7035 - light grey
- High corrosion protection
- Can also be used indoors depending on defined fire load see TRG 280, BGR 120 and TRGS 526
- Storage and operation even without compliance of protection zones as per TRG 280
- Roof inclined towards front
- Stainless steel floor to prevent impact damage
- Stainless steel base plate Niro Rhombus
- Ventilation slots in door(s) and below projecting roof
- Cabinet roof prepared for on-site technical forced ventilation system DN 75
- Door(s) with cylinder lock
- Marked with warning symbol W19
- Fully equipped TRG cells:
 - 2 x vertical c-rails on back wall
 - 2 x height- adjustable, horizontal c-rails for mounting fittings
 - 1 x cylinder holder (tension belt) for 50 liters gas cylinders
 - Outlets in roof for pipe penetration (ø 25 mm) including filler plug



TRG 1400, Article No. C27-3301-B



Further information and accessory can be found on page 147!



TRG 700, Article No. C27-3300-B



TRG 1050, Article No. C27-3302-B



TRG 700, Article No. C27-3306-B

Model	TRG 700	TRG 1050	TRG 1400
External dimensions W x D x H (mm)	700 x 400 x 2150	1050 x 400 x 2150	1400 x 400 x 2150
Door/s	1, hinged right	double door	double door
Pipe penetrations	5	8	10
Capacity 50 liter gas cylinders	up to 2	up to 3	up to 4
Weight (kg)	65	90	120
Outer body: RAL 7035 - light grey			
Article No., door/s sheet steel RAL 7035 - light grey	С27-3300-В	С27-3302-В	С27-3301-В
Article No., door/s sheet steel RAL 7035 - light grey with plexiglass segment	C27-3306-B	C27-3307-B	С27-3308-В