



**LACONT FIRE PROTECTION CONTAINER - WALK-IN PREMIUM**

**Execution:**

Technically as WSC Classic on page 179, but **internal height 2120 mm** and usable **storage depth 2550 mm**.



**WSC 6-PR/F90,  
Article no. C64-4031-B,  
with double door**

**i** Accessories such as forced ventilation, heating, illumination and shelving can be found on page 179!

Model	WSC 2-PR/F90	WSC 3-PR/F90	WSC 4-PR/F90	WSC 5-PR/F90	WSC 6-PR/F90	WSC 7-PR/F90	WSC 8-PR/F90
External dimensions W x D x H (mm)	2170 x 2950 x 2440	3000 x 2950 x 2440	4000 x 2950 x 2440	5000 x 2950 x 2440	6000 x 2950 x 2440	7000 x 2950 x 2440	8000 x 2950 x 2440
Internal dimensions W x D x H (mm)	1930 x 2550 x 2120	2750 x 2550 x 2120	3750 x 2550 x 2120	4750 x 2550 x 2120	5750 x 2550 x 2120	6750 x 2550 x 2120	7750 x 2550 x 2120
Sump capacity (l)	700	1000	1400	1800	2 x 1100	2 x 1300	2 x 1500
Max. load (kg/m <sup>2</sup> )	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	C64-4022-B	C64-4024-B	C64-4026-B	C64-4028-B	C64-4030-B	C64-4032-B	C64-4034-B
Article no. door W x H (mm) 1750 x 2000 (DD)**	C64-4023-B	C64-4025-B	C64-4027-B	C64-4029-B	C64-4031-B	C64-4033-B	C64-4035-B

\* SD = single door    \*\* DD = double door

**LACONT FIRE PROTECTION CONTAINER - WALK-IN SUPERIOR**



**WSC 4-SU/F90,  
Article no. C64-4054-B,  
with single door**



**Execution:**

Technically as WSC Classic on page 179, but with the largest storage volume of all WSCs, **internal height 2520 mm** and usable **storage depth 2550 mm**.

**i** Accessories such as forced ventilation, heating, illumination and shelving can be found on page 179!

Model	WSC 2-SU/F90	WSC 3-SU/F90	WSC 4-SU/F90	WSC 5-SU/F90	WSC 6-SU/F90	WSC 7-SU/F90	WSC 8-SU/F90
External dimensions W x D x H (mm)	2170 x 2950 x 2840	3000 x 2950 x 2840	4000 x 2950 x 2840	5000 x 2950 x 2840	6000 x 2950 x 2840	7000 x 2950 x 2840	8000 x 2950 x 2840
Internal dimensions W x D x H (mm)	1930 x 2550 x 2520	2750 x 2550 x 2520	3750 x 2550 x 2520	4750 x 2550 x 2520	5750 x 2550 x 2520	6750 x 2550 x 2520	7750 x 2550 x 2520
Sump capacity (l)	700	1000	1400	1800	2 x 1100	2 x 1300	2 x 1500
Max. load (kg/m <sup>2</sup> )	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	C64-4050-B	C64-4052-B	C64-4054-B	C64-4056-B	C64-4058-B	C64-4060-B	C64-4062-B
Article no. door W x H (mm) 1750 x 2000 (DD)**	C64-4051-B	C64-4053-B	C64-4055-B	C64-4057-B	C64-4059-B	C64-4061-B	C64-4063-B

\* SD = single door    \*\* DD = double door