Explanations see practical informations on page 6 and 84!

LACONT FIRE PROTECTION CONTAINER - WALK-IN COMFORT

Execution:

Technically as WSC Classic on page 179, but **internal height 2520 mm** and usable **storage depth 2100 mm.**

MVV TB Nr. C2.15.12
Ü
steel troughs guidelines
TüV-Nord systems
DIBt Berlin

EI 90

◆ Fire protection container with components according to DIN EN 13501 (EI 90)

◆ **Suitable for indoor and outdoor use**

◆ Steel sumps as per WHG with grid cover

◆ Doors close automatically if fire occurs

◆ Lifting attachments for cranes (for empty transport only) as standard

Ex-proof heating

**WSC 4-CO/F90,
Article no. C64-4040-B,
with single door and
optional drive-on ramp**

Equipped with shelving for use as small container store

i

Accessories such as forced ventilation, heating, illumination and shelving can be found on page 179!

Model	WSC 2-CO/F90	WSC 3-CO/F90	WSC 4-CO/F90	WSC 5-CO/F90	WSC 6-CO/F90	WSC 7-CO/F90	WSC 8-CO/F90
External dimensions W x D x H (mm)	2170 x 2500 x 2840	3000 x 2500 x 2840	4000 x 2500 x 2840	5000 x 2500 x 2840	6000 x 2500 x 2840	7000 x 2500 x 2840	8000 x 2500 x 2840
Internal dimensions W x D x H (mm)	1930 x 2100 x 2520	2750 x 2100 x 2520	3750 x 2100 x 2520	4750 x 2100 x 2520	5750 x 2100 x 2520	6750 x 2100 x 2520	7750 x 2100 x 2520
Sump capacity (l)	600	800	1200	1400	1800	2 x 1100	2 x 1200
Max. load (kg/m²)	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	**C64-4036-B**	**C64-4038-B**	**C64-4040-B**	**C64-4042-B**	**C64-4044-B**	**C64-4046-B**	**C64-4048-B**
Article no. door W x H (mm) 1750 x 2000 (DD)**	**C64-4037-B**	**C64-4039-B**	**C64-4041-B**	**C64-4043-B**	**C64-4045-B**	**C64-4047-B**	**C64-4049-B**

* SD = single door   ** DD = double door