



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20805500

25kg Purple K Powder Stored

Pressure Trolley Fire Extinguisher



Extinguisher Model	C-25PKTP
Extinguishing Medium	Purple K Dry Chemical Powder
Propellant Type	Stored Pressure
Capacity	25kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	B,C & Electrical
Operating Temperature	-20 °C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	14kgf/cm ²
Discharge Time	40 Sec
Discharge Range	10 meters
Safe Operating Range	6 meters
Discharge Hose	6 meters with controllable discharge gun
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	CE Approved Brass Turn Valve
Height	920mm
Diameter	420mm
Full Weight	45kg
Empty Weight	20kg
Standards	BS EN 1866

