



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20800200

4KG Halotron I Stored Pressure Fire Extinguisher



Extinguisher Model	C-4HSE
Extinguishing Medium	Halotron™ I
Propellant Type	Argon
Capacity	4.0kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B,C & Electrical
Fire Rating	8A/55B
Operating Temperature	-20 °C to +60 °C
Test Pressure	25 bar
Max Working Pressure	8.63kgf/cm ²
Minimum Discharge Time	9.2 Sec
Minimum Discharge Range	5 meters
Safe Operating Distance	2 meters
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	Forged / Brass
Height (+/-3mm)	473mm
Diameter	139mm
Full Weight	6.53kgs
Empty Weight	2.53kgs
Approval	PSB

