



LINGJACK ENGINEERING WORKS PTE LTD

No.1 Woodlands Terrace, Lingjack Industrial Building, Singapore 738471

Tel : (65) 67594163 Fax : (65) 67587513 Web site: www.combat.com.sg

Co Reg No. : 199103053M GST Reg no. : M2-0100375-0

Data Sheet No.: 20802000

75kg ABC Powder Stored Pressure Trolley Fire Extinguisher



Extinguisher Model	C-75ATP
Extinguishing Medium	ABC Dry Chemical Powder
Propellant Type	Stored Pressure
Capacity	75kg
Paint Primer/Finish	Zinc phosphate/ Epoxy polyester
Paint Colour	Signal Red (RAL3000)
Fire Class	A,B,C & Electrical
Fire Rating	III B
Operating Temperature	-20 °C to +60 °C
Test Pressure	25kgf/cm ²
Max Working Pressure	14kgf/cm ²
Discharge Time	55 Sec
Discharge Range	14 meters
Safe Operating Range	6 meters
Discharge Hose	6 meters with controllable discharge gun
Cylinder Material	Cold Rolled Steel Sheet
Operating Valve	CE Approved Turn Valve
Height	1172mm
Diameter	740mm
Full Weight	135kg
Empty Weight	60kg
Standards	BS EN 1866

