• CO₂ EXTINGUISHERS

 CO_2 is suitable for fires in electrical equipment, class B, and is recognised for its non-damaging highly effective performance and cleanliness. CO_2 displaces oxygen and has a smothering effect on fire. The CO_2 gas is condensed and keeps a temperature of approximately - 78°C at discharge. When using larger CO_2 units indoors, be aware that CO_2 in high concentration can displace and reduce the oxygen-level in the room. This can be hazardous to life and health. 1 kg CO_2 gives approximately 560 liter CO_2 gas. 15 - 20% CO_2 mixture is hazardous. 28% mixture reduces the O_2 level down to 15%. Hold all necessary approvals for the respective models.

HAND-HELD CO2 EXTINGUISHERS



NOHA K2G

2 kg CO₂ extinguisher in aluminum. Contains 2 kg CO₂. Areas of application include computer rooms, technical rooms, next to fuse terminal boxes, and other electronic equipment.

NOHA AK 2-Z

2 kg $\rm CO_2$ extinguisher in aluminum, with long snowhorn.



NOHA K5G

5 kg CO₂ extinguisher in aluminum, with long snowhorn. Contains 5 kg CO₂. Areas of application include computer rooms, technical rooms, next to fuse terminal boxes, and other electronic equipment.

WHEELED CO2 EXTINGUISHERS



NOHA K10

Wheeled 10 kg CO2 extinguishers. NOHA K10 contains 10 kg CO2, and has a 5 m hose. Areas of application include heli-deck, power aggregate, and switchboard room.



NOHA K20

Wheeled 20 kg CO2 extinguishers. NOHA K20 contains 20 kg CO2, and has a 5 m hose. Areas of application include heli-deck, power aggregate, and switchboard room.

Model	Risk	Effect	MED	Effective	Total	Dimentions	Order number
	class	class	o	discharge time	weight	$L \times VV \times H (mm)$	
NOHA AK 2	В	34B	Ja	19 sec.	7 kg	117 x 310 x 520 ³	320 025
NOHA AK 2-Z	В	34B	Ja	19 sec.	7 kg	117 x 310 x 520³	320 029
NOHA AK 5	В	89B	Ja	17 sec.	14 kg	152 x 265 x 670 ³	320 124
NOHA K10	В	144 IV B	Ja	17 sec.	38 kg	1045 x 350 x 900	310 716
NOHA K20	В	144 IV B	Ja	32 sec.	38 kg	600 x 410 x 965	310 717

³ Including snowhorn

OBS1: Old nr 420029 replaced with new 320025 " 420025 " 320125