


# • NOHA MODEL S11 & S11SW



## NOHA FIXED OFFSHORE HOSE REEL FOR WALL-MOUNTING

Gunmetal piping parts, for sea water.

For use in accommodation and living quarters, drilling areas, production areas offshore and at petrochemical plants.



Model	Hose Length	Dimensions in mm Ø x D	Order number	Dry Weight
	25 mm			
S11	0 m	550 x <b>230</b>	400 001	12 kg
S11	20 m	550 x <b>230</b>	400 002	30 kg
S11	0 m	550 x 275	400 003	12 kg
S11	25 m	550 x 275	400 004	35 kg
S11	0 m	650 x 275	400 005	13 kg
S11	30 m	650 x 275	400 006	40 kg
S11	0 m	700 x 175	400 007	14 kg
S11	20 m	700 x 175	400 008	32 kg
S11	0 m	700 x 220	400 009	14 kg
S11	25 m	700 x 220	400 010	37 kg

### NOHA MODEL S11 IS SUPPLIED WITH:

- Hose reel made of galvanized steel
- Piping parts gunmetal
- Paint according to NOHA offshore specification for galvanized steel, RAL 3000 red
- Oil resistant, antistatic rubber hose with working pressure 20 bar, and pressed SST hose couplings
- Water supply through the centre of the reel
- Hose coupling reel end: 1" BSP female, swivel, gunmetal
- Hose coupling nozzle end: 1" BSP male, fixed, gunmetal
- Bolts and nuts in stainless steel
- Water inlet 1" BSP male
- Design pressure 20 bar
- Design temperature -9/+35°C
- NOHA installation instructions
- *Nozzle, stop valve and documentation are not included*
- **Options:** See page 13-15



## NOHA SWINGING OFFSHORE HOSE REEL FOR WALL-MOUNTING

Gunmetal/stainless steel piping parts, for sea water.

For use in accommodation and living quarters, drilling areas, production areas offshore and at petrochemical plants.

### NOHA MODEL S11SW IS SUPPLIED WITH:

- Hose reel made of galvanized steel
- Piping parts gunmetal/stainless steel
- Paint according to NOHA offshore specification for galvanized steel, RAL 3000 red
- Oil resistant, antistatic rubber hose with working pressure 20 bar, and pressed SST hose couplings
- Mounting template
- NOHA swinging arm with internal waterways, hinged on right hand side
- Hose coupling reel end: 1" BSP female, swivel, gunmetal
- Hose coupling nozzle end: 1" BSP male, fixed, gunmetal
- Water inlet 1" BSP male
- Bolts and nuts in stainless steel
- Design pressure 20 bar
- Design temperature -9/+35°C
- NOHA installation instructions
- *Nozzle, stop valve and documentation are not included*
- **Options:** See page 13-15

Model	Hose Length	Dimensions in mm W x H x D	Order number	Dry Weight
	25 mm			
S11SW	0 m	715 x 650 x 235	560 208	17 kg
S11SW	20 m	715 x 650 x 235	560 209	35 kg
S11SW	25 m	715 x 650 x 235	560 202	40 kg
S11SW	30 m	715 x 650 x 235	560 203	44 kg

