

TURBOKADOR SELECTABLE GALLONAGE

Nozzles and Tips in Hardcoat Anodized Aluminum and PTFE

The TURBOKADOR offers a durable, lightweight selectable gallonage nozzle with the features that you are looking for. Machined out of high-grade aluminum alloy with the trademarked NITUFF™ finish that gives 50 microns of PTFE impregnated anodized unlike the 20 microns of standard anodized. The standard shutoff ball is also coated using the NITUFF process, which provides years of smooth action with minimal wear.

The TURBOKADOR offers flow ranges from 10 GPM to 350 GPM in a 1.0", 1.5" and 2.5" size. All sizes come with a double ball bearing swivel for ease in connection and use. A built in stream shaper/strainer is also installed on every model. A key feature of the TURBOKADOR is its ability to be easily changed from straight stream to narrow fog to wide-angle fog to flush without having to shutdown.

Fully compliant with NFPA 1964, the TURBOKADOR also offers customizing with color-coded bumper, pistol grip and shutoff handle as well as type of teeth. Comes standard with a black bumper guard and pistol grip. All TURBOKADORS are available in tip only configuration or without pistol grip.

or grip.							
Code	Description	W	н	L	Weight	FLOW	
						GPM	LPM
2310	TURBOKADOR 150 nozzle 1.5" inlet	4.5"	10.5"	9.0"	4.0 lb	10-20-25-40	40-75-100-150
2311	TURBOKADOR 150 nozzle 1.0" inlet	4.5"	10.5"	9.0"	3.8 lb	10-20-25-40	40-75-100-150
9891	TURBOKADOR 500 nozzle 1.5" inlet	4.5"	10.5"	10.5"	5.0 lb	30-60-95	100-200-300
9892	TURBOKADOR 500 nozzle 1.5" inlet	4.5"	10.5"	10.5"	5.0 lb	60-95-125	150-300-500
8370	TURBOKADOR 500 nozzle 1.5" inlet	4.5"	10.5"	10.5"	5.0 lb	30-60-95-125	100-200-300-500
10648	TURBOKADOR 750 nozzle 1.5" or 2.5" inlet	5.0"	10.5"	10.5"	7.8 lb	95-125-150-200	300-500-750-1000
9724	TURBOKADOR 1000 nozzle 2.5" inlet	6.0"	15.0"	16.5"	11.0 lb	100-150-200-250	350-500-750-1000
9996	TURBOKADOR 1000 nozzle 2.5" inlet	6.0"	15.0"	16.5"	11.0 lb	200-250-300-350	750-1000-1150-1350
13133	TURBOKADOR 150 tip 1.0" inlet	2.7"	2.7"	6.5"	2.2 lb	10-20-25-40	40-75-100-150
9953	TURBOKADOR 150 tip 1.5" inlet	2.7"	2.7"	6.5"	2.4 lb	10-20-25-40	40-75-100-150
9954	TURBOKADOR 500 tip 1.5" inlet	3.7"	3.7"	6.5"	3.4 lb	30-60-95	100-200-300
9952	TURBOKADOR 500 tip 1.5" inlet	3.7"	3.7"	6.5"	3.4 lb	60-95-125	150-300-500
8370T	TURBOKADOR 500 tip 1.5" inlet	3.7"	3.7"	6.5"	3.4 lb	30-60-95-125	100-200-300-500
9974	TURBOKADOR 750 tip 1.5' or 2.5" inlet	5.0"	5.0"	7.5"	5.4 lb	95-125-150-200	300-500-750-1000
8346	TURBOKADOR 1000 tip 1.5" inlet	5.0"	5.0"	5.8"	5.8 lb	100-150-200-250	350-500-750-1000
9975	TURBOKADOR 1000 tip 2.5" inlet	4.6"	5.0"	7.5"	3.2 lb	200-250-300-350	750-1000-1150-1350