

FIRE EXTINGUISHERS PORTABLE DRY CHEMICAL

Model/Series No. 3000 SERIES **3300 SERIES**

Member of Morris Group International™

SPECIFICATIONS

ABC MULTI-PURPOSE DRY CHEMICAL

Red glossy polyester coated steel cylinder with pressure gauge, wall mounting bracket and hose or nozzle as indicated. Non conductive siliconized mono ammonium phosphate dry chemical. Contents stored under pressure at approximately 195 PSI.

PURPLE K DRY CHEMICAL

Red glossy polyester coated steel cylinder with hose, squeeze grip control nozzle and wall mounting bracket. Electrically non conductive siliconized potassium bicarbonate dry chemical. Contents stored under pressure at approximately 195 PSI.



PRODUCT OPTIONS

SEE 3900 SERIES CATALOG FOR OPTIONAL FIRE **EXTINGUISHER MOUNTING BRACKETS.**

MODEL SELECTION

☐ 3002 ABC Dry Chemical

☐ 3005 ABC Dry Chemical

☐ 3005-3 ABC Dry Chemical

☐ 3006 ABC Dry Chemical

☐ 3010 ABC Dry Chemical

☐ 3020 ABC Dry Chemical

☐ 3302-PK Purple K Dry Chemical

☐ 3305-PK Purple K Dry Chemical

☐ 3310-PK Purple K Dry Chemical

☐ 3320-PK Purple K Dry Chemical

Project:	Model #:	POTTER ROEMER
Contractor:	Quantity:	Headquarters: Also in: P.O. Box 3527 New York (800) 526-4592 City of Industry, CA Chicago (800) 547-3473
Distributor:	Approved by:	91744 U.S.A. Atlanta (800) 762-0542 Los Angeles Area Miami (833) 744-3473
Architect:	Date:	800-366-3473 Dallas (866) 644-3473 626-855-4890 www.potterroemer.com

FIRE EXTINGUISHERS PORTABLE DRY CHEMICAL

Model/Series No.
3000 SERIES
3300 SERIES

MODEL DATA CHARTS

Member of Morris Group International™

ABC MULTI-PURPOSE DRY CHEMICAL									
Model No.	Size lbs./ kg	U/L Rating	Height	Diameter	Range of Stream	Type Discharge			
3002	2-1/2 / 1.1	1A:10B:C	15-1/2"	3"	9'-15'	Nozzle			
3005	5 / 2.3	2A:10B:C	15-1/4"	4-1/4"	12'-18'	Hose & Nozzle			
3005-3	5 / 2.3	3A:40B:C	15-1/4"	4-1/4"	12'-18'	Hose			
3006	6 / 2.7	3A:40B:C	16"	5"	15'-21'	Hose			
3010	10 / 4.5	4A:80B:C	20"	5"	15'-21'	Hose			
3020	20 / 9	10A:120B:C	24"	7"	15'-21'	Hose			



PURPLE K DRY CHEMICAL								
Model No.	Size lbs. / kg	U/L Rating	Height	Diameter	Range of Stream	Type Discharge		
3302-PK	2 1/2 / 1.13	10B:C	15-1/2"	3"	9'-15'	Hose		
3305-PK	5 / 2.3	30B:C	15-1/4"	4-1/4"	12'-18'	Hose		
3310-PK	10 / 4.5	80B:C	20-1/2"	5"	15'-21'	Hose		
3320-PK	20 / 9	120B:C	24"	7"	15'-21'	Hose		



Call Potter Roemer for current listings and approvals.
Dimensions are subject to manufacturer's tolerance and
may change without notice. Potter Roemer assumes no
responsibility for use of void or superceded data. ©
Copyright Potter Roemer, Member of Morris Group
International ™ Please visit potterroemer.com for most
current specifications.





04/11/2023













POTTER ROEMER

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473