

SPECIFICATIONS

Potter Roemer/ Fire Pro® Master Stream adjustable flow-baffle monitor nozzles are combination pattern, master stream nozzles with selectable flow settings. Precision machining ensures ease of operation when changing patterns at all pressure ranges.



REGULARLY FURNISHED

- Combination fog and straight stream
- Lightweight/strong alloy or brass construction
- Fixed teeth
- Built-in stream shaper for maximum reach

MODEL	INLET In (mm)	LENGTH In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP10822	2-1/2" (65)	6-3/4" (170)	4-3/8 (2)	250, 350, 500 (946, 1325, 1893)
*FP10822-BC	2-1/2" (65)	6-3/4" (170)	4-3/8 (2)	250, 350, 500 (946, 1325, 1893)
FP10823	2-1/2" (65)	6-3/4" (170)	4-3/8 (2)	300, 500, 700 (1136, 1893, 2650)
*FP10823-BC	2-1/2" (65)	6-3/4" (170)	4-3/8 (2)	300, 500, 700 (1136, 1893, 2650)

* FM Approved

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications</p> <p>MS-FP10822 Revised: 09/05/18</p>	<p>MEMBERSHIP</p> 	<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	---	---