



SPECIFICATION SHEET

280-EVSV-CH

LIGHTWEIGHT INDUSTRIAL HEIGHT SAFETY HELMET WITH 4-POINT CHIN STRAP FOR WORKING AT HEIGHTS, INTEGRATED ANSI Z87.1 EYE PROTECTION, EPS IMPACT LINER, 6-POINT POLYESTER SUSPENSION WITH WHEEL RATCHET ADJUSTMENT

- Fully adjustable four-point chinstrap for working at heights
- EPS Impact Liner
- Fully retractable integrated eye protector. ANSI Z87+ Impact Resistant
- Vistashield pivots smoothly allowing the wearer to adjust the faceshield position maximising coverage and protection
- 6-Point polyester textile suspension system offers unrivaled comfort without compromising performance
- Revolution™ Wheel Ratchet is easy to use and creates a firm comfortable fit
- Meets ANSI/ISEA Z89.1, Type I, Class C requirements
- Meets EN12492 – Mandatory Shock Absorption and Penetration – Front, Sides and Rear
- Universal accessory slots accepts virtually any competitors' accessories
- Chamlon™ sweatband

APPLICATIONS

Protection from falling debris and low hanging objects in industrial and construction applications.

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: ABS Suspension: HDPE strap & clips, polyester straps Sweatband: Cotton core with PU coating
COLOR	01W - ☐ White ☐ White Front 01S - ☐ White ☐ Smoke Front 11SR - ☒ Black ☐ Smoke Front with Silver CR2 Reflective Kit
SIZES	Adjustable
WEIGHT	1.32 lbs / 600 g
PACKAGING	Individually bagged, 10 per case
CASE	9.5" x 23" x 18" / 24.1 cm x 58.4 cm x 45.7 cm
CASE WEIGHT	13.22 lbs / 6 kg
COO	UK

BARCODES

ITEM	EACH	CASE
☐ 280-EVSV-CH-01W	5038428417778	5038428417785
☐ 280-EVSV-CH-01S	5038428417792	5038428417808
☒ 280-EVSV-CH-11SR	5038428418140	5038428418157



DIMENSIONS (in/cm)

	OSFA
A	11.02 / 28
B	5.9 / 15

