



## Capacitive Evaluation Unit Series 250 - 115V / 230V AC

- Housing 40 x 70 x 110 mm  
 • For capacitive sensors KS-250-M22...M32

Certificate:



### Technical data

Output function	1 x change-over contact	1 x change-over contact
<b>Type</b>	<b>KSA-250 for 2 m</b>	<b>KSA-250 for 2 m</b>
<b>Art.-No.</b>	<b>560 101</b>	<b>560 100</b>
<b>Type</b>	<b>KSA-250 for 5 m</b>	<b>KSA-250 for 5 m</b>
<b>Art.-No.</b>	<b>560 106</b>	<b>560 102</b>
Operating voltage ( $U_B$ )	90...130 V AC	200...250 V AC
Contact rating each relay max.	250 V / 6 A / 500 VA	250 V / 6 A / 500 VA
Power consumption	Typ. 3.5 VA	Typ. 3.5 VA
Permitted ambient temperature	-20...+60 °C	-20...+60 °C
LED-display	Yellow	Yellow
Protective circuit	Built-in	Built-in
Degree of protection IEC 60529	IP 20	IP 20
Norm	EN 60947-5-2	EN 60947-5-2
Connection	Screw terminals and Triax-socket	Screw terminals and Triax-socket
Housing material	ABS	ABS

All specifications are subject to change without notice. (06/2014)

