

Heavy Duty Spring Retractable Hose Reels

Air/Water/Oil/Grease - 1/4", 3/8", 1/2", 3/4" I.D.

- Compact design - reels are 25% smaller than our Series 80000 reels
- Redesigned latching mechanism provides longer service life of the latch components
- Containerized drive spring offers easier handling during maintenance
- High quality, die-cast aluminum hub and two sealed ball bearings produce a smoother spool rotation and easier operation
- Guide arm adjusts to seven positions



HD76100 OLP



HD78005 OLP

Additional Series HD70000 Models

Enclosed Reels - Page 11 **Pressure Wash** - Page 23
S.S. Fluid Path - Page 18 **Cord Reels** - Page 29-31
Fuel/DEF - Page 20-21 **Welding Gas** - Page 34-35
Twin Hydraulic - Page 22



Model with hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure	NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index #
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in
Low Pressure Air/Water Reels Maximum Temperature 150 °F (65 °C) Max working pressure is at 70 °F (20 °C)													
HD76050 OLP	45	20	3/8	10	.600	15	50	15	300	21	1/4	1/2	1/2
HD76070 OLP	49	22	3/8	10	.600	15	70	21	300	21	1/4	1/2	1/2
HD76075 OLP	65	29	3/8	10	.600	15	75	23	300	21	1/4	1/2	2
HD76100 OLP	75	34	3/8	10	.600	15	100	30	300	21	1/4	1/2	2
HD78050 OLP	49	22	1/2	13	.750	19	50	15	300	21	3/8	1/2	1/2
HD78075 OLP	73	33	1/2	13	.750	19	75	23	300	21	3/8	1/2	2
HD79025 OLP	49	27	3/4	19	1.075	27	25	8	250	17	3/4	3/4	1
Medium Pressure Oil Reels Maximum Temperature 210 °F (99 °C)													
HD76050 OMP	57	26	3/8	10	.690	18	50	15	2600	179	3/8	1/2	1/2
HD76075 OMP	85	39	3/8	10	.690	18	75	23	2600	179	3/8	1/2	1/2
HD78050 OMP	59	27	1/2	13	.820	21	50	15	3000	207	1/2	1/2	1/2
High Pressure Grease Reels Maximum Temperature 210 °F (99 °C)													
HD74050 OHP	57	26	1/4	6	.580	15	50	15	5000	345	1/4	1/2	3/8
HD74075 OHP	80	36	1/4	6	.580	15	75	23	5000	345	1/4	1/2	3/8
HD74100 OHP	86	39	1/4	6	.580	15	100	30	5000	345	1/4	1/2	3/8
HD76050 OHP	62	28	3/8	10	.730	19	50	15	4800	331	1/4	1/2	3/8
HD76075 OHP	90	41	3/8	10	.730	19	75	23	4800	331	1/4	1/2	3/8

Low pressure reels furnished standard with PVC hose. Medium pressure reels furnished standard with S.A.E. 100R1-AT (3/8") or S.A.E. 100R17 (1/2") one wire braid hose. High pressure reels furnished standard with S.A.E. 100 R2T two wire braid hose.

Dimensions - Size Index				
	1		2	
	in	mm	in	mm
A	20 1/4	514	20 1/4	514
B	19 3/4	502	19 3/4	502
C	7 13/16	198	7 13/16	198
D	3 7/8	98	3 7/8	98
E	7	178	8 1/4	210

Model without hose & bumper	Shipping Weight		Hose Capacity				Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index #
	lbs	kg	I.D.	O.D.	Length		psi	bar	in	in
			in	mm	in	mm				
Low Pressure Air/Water Reels Maximum Temperature 210 °F (99 °C)										
HD76000 OLP	42	19	3/8	10	.600	15	70	21	500	35
HD76005 OLP	56	25	3/8	10	.600	15	100	30	500	35
HD78000 OLP	43	20	1/2	13	.750	19	50	15	500	35
HD78005 OLP	58	26	1/2	13	.750	19	75	23	500	35
Medium Pressure Oil Reels Maximum Temperature 210 °F (99 °C)										
HD78000 OMP	43	20	1/2	13	.820	21	50	15	3000	207
High Pressure Grease Reels Maximum Temperature 210 °F (99 °C)										
HD74005 OHP	60	27	1/4	6	.580	15	100	30	5000	345
HD76005 OHP	60	27	3/8	10	.730	19	75	23	5000	345

NEW!
Reel Covers

See page 41



Interactive Reel Catalog

Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.



Pivot Bases & Swing Brackets

See page 43