

Premium Duty Spring Retractable Hose Reels

Series B3000 - Air/Water - 1/4", 3/8" I.D.

Reelcraft's Series 3000 reels are all-steel, powder coated construction and ultra-compact for a wide range of bench mount or mobile applications with critical space requirements. These compact reels easily fit within a 1 ft. x 1 ft. space. The reels incorporate multiple slotted mounting holes to accommodate many configurations. An optional guide arm accessory is available for multiple adjustment positions of the hose.

NEW!



B3415 OLP



S602805 -
Optional guide
arm accessory

Model with hose	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Hose Outlet	NPT(F) Reel Inlet
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in
Low Pressure Air / Water Hose Reels Maximum temperature 150 °F (65 °C)												
B3415 OLP	17	7.7	1/4	6	.475	12	15	4.6	300	21	1/4	3/8
B3425 OLP	18	8.2	1/4	6	.475	12	25	7.6	300	21	1/4	3/8
B3610 OLP	17	7.7	3/8	10	.600	15	10	3.0	300	21	1/4	3/8
B3620 OLP	18	8.2	3/8	10	.600	15	20	6.1	300	21	1/4	3/8
S602805	1.1	0.5	Optional guide arm accessory for multiple adjustment positions.									

Low pressure reels furnished standard with PVC hose.

Under Bench Mount		Dimensions	
		in	mm
A		11 ³ / ₁₆	284
B		11 ¹ / ₁₆	281
C		6	152
D		8	203
E		4 ³ / ₁₆	106
F		6	152
G		2 ¹ / ₂	64

Premium Duty Enclosed Hose Reels

Series 5000/7000 - 1/4", 3/8" I.D.

Enclosed reels feature a steel enclosure that offers an additional level of protection for the hose from potentially harmful foreign debris. These reels are designed such that removing the cover on either side will allow access to the majority of serviceable parts.

Made
in USA



5635 ELP

		Dimensions			
		5000 E		7000 E	
		in	mm	in	mm
A		15	381	20 ⁷ / ₈	530
B		16 ¹ / ₄	413	21 ¹ / ₈	537
C		9 ³ / ₄	248	7 ¹³ / ₁₆	198
D		2 ¹ / ₂	64	3 ⁷ / ₈	98
E		7	178	7 ⁵ / ₈	194

Model with Hose	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		**Max Pressure		NPT(M) Hose Outlet		NPT(F) Reel Inlet		Model without hose & bumper		Shipping Weight		Pressure		
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in		in				lbs	kg	psi	bar	
Low Pressure Air/Water Reels Maximum temperature 150 °F (65 °C) **Maximum working pressure at 70 °F (20 °C)																					
5450 ELP	34	15	1/4	6	.475	12	50	15	300	21	1/4		3/8		5400 ELP	25	11	500	35		
5635 ELP	33	15	3/8	10	.600	15	35	11	300	21	1/4		3/8		5600 ELP	29	13	500	35		
7650 ELP	60	27	3/8	10	.600	15	50	15	300	21	1/4		1/2		7600 ELP	57	26	500	35		
Medium Pressure Oil Reels Maximum temperature 210 °F (99 °C)																					
5630 EMP	39	18	3/8	10	.690	18	30	9	2600	179	3/8		3/8		5600 EMP	32	15	3000	207		
7650 EMP	72	33	3/8	10	.690	18	50	15	2600	179	3/8		1/2		7600 EMP	60	27	3000	207		
High Pressure Grease Reels Maximum temperature 210 °F (99 °C)																					
5625 EHP	40	18	3/8	10	.730	19	25	8	4800	331	1/4		1/4		5600 EHP	34	15	5000	345		
7450 EHP	72	33	1/4	6	.580	15	50	15	5000	345	1/4		1/2		7400 EHP	60	27	5000	345		

Low pressure reels furnished standard with PVC hose. Medium pressure reels furnished standard with S.A.E. 100R1-AT one wire braid hose. High pressure reels furnished standard with S.A.E. 100 R2T two wire braid hose. Models without hose maximum temperature is 210 °F (99 °C). Visit reelcraft.com for additional sizes and capacities.

Visit reelcraft.com/quick-ship for a complete list of Quick Ship Reels - models that can be shipped same day when the order is received by 1:00 PM Eastern Time for quantities of 10 or fewer.



Interactive Reel Catalog

Visit www.reelcraft.com/catalog for complete product specifications, available parts and accessories.

Prop 65: ⚠ WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov.