



**EXTINGUISHER**  
 REMOVE SAFETY PIN  
 DIRECT HORN AT  
 BASE OF FIRE  
 SQUEEZE HANDLE  
 TO DISCHARGE

**REMOVE SAFETY PIN**  
**DIRECT HORN AT**  
**BASE OF FIRE**  
**SQUEEZE HANDLE**  
**TO DISCHARGE**

**CE0086**  
 MODEL CD 50

Regularly, at least monthly, inspect the extinguisher for damage, corrosion, if there is any, for further leakage, and for other defects. If the extinguisher should be inspected, it should be inspected by a trained person.

If the gross weight of the extinguisher is less than the weight of the full extinguisher, it should be recharged. After use, the extinguisher should be recharged and inspected.

**WARNING**  
 Do not use the extinguisher outside the approved temperature range. Do not use the extinguisher for purposes other than those intended. Do not use the extinguisher for anything other than fire fighting. Do not use the extinguisher for anything other than fire fighting.

**WILSON**  
 FIRE EQUIPMENT CO.  
 1000 W. 10th St.  
 Tulsa, OK 74103  
 (918) 438-1234



# CO<sub>2</sub>

## Extinguishers

Model	A	B	C	D	F
CD 2G		21 B			
CD 5G		55 B			

### Product description

SFFECO CO<sub>2</sub> gas extinguishers are characterised by their high performance for fires involving an electrical risk like computers, office equipment and generators etc. CO<sub>2</sub> is non-conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings.

Suitable for Class B fire risks

### Features:

- Carbon Dioxide, gases agent, colorless, odorless, non-Toxic provide rapid knock down of industrial fire. Capable of fighting Class B fire.
- Kite Mark Certified to BS EN 3
- Seamless Steel body (Lightweight)
- High Quality Polyester Powder Coated Paint
- Controlled Discharge
- Brass head valve with simple squeeze operations provided with pressure relieve disc.
- Rechargeable & easy to service.
- Non conductive agent for electrical use without risk to operator
- CO<sub>2</sub> gas disappears quickly leaving no residue
- Swivel horn with no freeze burn, with greater directional control of CO<sub>2</sub> discharge through horn rotation feature.
- 2Kg is available now with the 55 B Fire rating as efficient as 5Kg unit.

**Ideal Use:** Chemical Manufacturing Plant, Oil Rigs, Rail Yards, Warehouses, Construction sites, parking garages, Airport, Boat & Docks and Large laboratories.



1. Valve / Extn. Lever
2. Safety Pin with chain
3. Valve Handle
4. Discharge Horn
5. Syphon Tube



Wall Bracket

MODEL	CD 5G	CD 2G
Capacity	5 Kg.	2 Kg.
Fire Rating	55B	21B
Average Discharge Time	9.5 Sec	9 Sec.
Height	720 mm	630 mm
Diameter	139.7 mm	101.6 mm
Filled Weight	17.5 kg.	8.2 kg.
Empty Weight	12.5 kg.	6.2 kg.
Operating Temperature	-20°C to + 60°C	-20°C to + 60°C
Maximum Service Pressure	169 bar	169 bar
Test Pressure	250 bar	250 bar

