STANFIELD'S LTD


P.O. Box 190 - 1 Logan Street Truro, Nova Scotia Canada B2N 5C2 902-895-5406 Fax: 902-893-8187 e-mail: inquiries@stanfields.com



Fire Safety Hood™







Measurements FH36	
A-B	18.0"
A-J	4.0"
C-D	8.0"
E-F	6.5"
G-H	10.0"
K-B	3.0"
I-L	11.0"
M-N	3.0"
H-L	9.0"
D-H	5.0"

Part Number: FH36

Fabric:

Content: 20/80 Nomex / Lenzing FR Weight: 7.0 oz sq yd Construction: 1x1 Rib Knit Stretch: 100% Color: White

Hood Design:

One Piece flared tube extends to hem with a shoulder notch. Layers: Two Measurements: See chart above

Face Opening:

Face Opening Sewn with ½ inch elastic Relaxed Measurement: 5 to 5.5 inches Fully Stretched Measurement: Exceeds 15 inches

Construction:

Head Seams: All head and bib seams sewn with flat lock stitch.

Face Opening: Elastic sewn to edge with three thread overlock stitch; turned under and sewn with a two needle cover stitch.

Bib Hem: The bib edge is hemmed with a crochet stitch.

Thread: 100% Nomex

Labels:

FR label. All four label edges sewn to the hood.

Certification:

Classified by Underwriters Laboratories to meet NFPA Standard 1971 2007 edition.

Test Results

NAPA

Thermal Protective Performance TPP

Before Washing:23.1After Washing:27.1

Flame Resistance Test One

After Flame Before Washing:0After Flame After Washing:0

Char Length Before Washing: 35 Char Length After Washing: 33

NFPA 1971-2007 Edition