LiteBox® Rechargeable Lantern

Case Material: High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle.

Dimensions/Weight: Length: 11 .5 in. (29.2 cm) Width: 5.1 in. (13 cm) Height: 7 in. (17.8 cm) / 7.4 lbs (3.36 kg)*

Light Source: High-intensity halogen bi-pin bulb available in 8 watt and 20 watt spot and flood PAR 36 assembly.

Light Output:

| <u> </u> | Peak Beam Candlepower (Maximum) | Bulb Lumens (Typical) |
|----------------|---------------------------------|--------------------------|
| Bi-pin bulb: | | |
| 8 watt flood | 1,500 | 150 |
| 20 watt flood | 3,000 | 400 |
| 8 watt spot | 80,000 | 150 |
| 20 watt spot | 105,000 | 400 |
| Dual Filament: | | |
| 8 watt spot | 70,000 each | 157 |



Battery/Run Time: Zero-maintenance 6V, 12Ah sealed lead acid operates up to nine hours per charge and is rechargeable up to 500 times.

Red and green LEDs give charge status feedback.

Models: Standard System - International safety orange or high-visibility yellow; includes shoulder strap; comes with AC and DC chargers and charge rack; ideal for field maintenance, inspection of construction sites, and remote equipment.

<u>Vehicle Mount System</u> - International safety orange or high-visibility yellow; comes with vehicle-mountable hard-wire rack and shoulder carrying strap.

<u>Power Failure System</u> - International safety orange or beige; comes with AC/DC chargers and "smart" power failure circuitry that automatically goes on when the power goes off.

<u>Dual Filament System</u> - International safety orange or high visibility yellow; features backup 8 watt safety spot; includes shoulder strap.

Approvals**: Most models meet applicable European Community Directives.

Rack meets requirements of NFPA 1901-12-1.7 mounted in any position.

Warranty: Limited lifetime warranty.

• 100V, 120V, or 240V AC (home) and 12V DC (automobile) charger cords.

Accessories:

• Hands-free shoulder strap (included in Standard & VM models)

• Locking charge rack; Quick release shoulder/waist strap

· Dual filament bulb providing instant backup available on Standard and Vehicle Mount systems

*With battery (included in purchase).

**See product for specific ratings.

| Item | UPC | Part # |
|---|------------------|--------|
| LiteBox Standard System AC/DC (8WS) Yellow | 080926-45117-9 | 45117 |
| LiteBox Standard System AC/DC (20WS) Yellow | , 080926-45109-4 | 45109 |
| LiteBox Standard System AC/DC (20WF) Yellow | 080926-45113-1 | 45113 |
| LiteBox Standard System AC/DC (8WS) Orange | e 080926-45116-2 | 45116 |
| LiteBox Standard System AC/DC (20WS) Orange | e 080926-45110-0 | 45110 |
| LiteBox Standard System AC/DC (20WF) Orange | 080926-45111-7 | 45111 |
| Dual Filament | - | |
| LiteBox Dual Filament Standard System AC/DC (8WS) Yellow | 080926-45705-8 | 45705 |
| LiteBox Dual Filament Standard System AC/DC (8WS) Orange | e 080926-45704-1 | 45704 |
| LiteBox Dual Filament Vehicle Mount System 12V DC (8WS) Yellow | 080926-45707-2 | 45707 |
| LiteBox Dual Filament Vehicle Mount System 12V DC (8WS) Orange | 080926-45706-5 | 45706 |

| Item | UPC | Part # | | |
|--|----------------|--------|--|--|
| LiteBox Vehicle Mount System 12V DC (8WS) Yellow | 080926-45108-7 | 45108 | | |
| LiteBox Vehicle Mount System 12V DC (20WS) Yellow | 080926-45104-9 | 45104 | | |
| LiteBox Vehicle Mount System 12V DC (8WS) Orange | 080926-45107-0 | 45107 | | |
| LiteBox Vehicle Mount System 12V DC (20WS) Orange | 080926-45102-5 | 45102 | | |
| Power Failure | | | | |
| LiteBox Power Failure System AC/DC chargers & mounting rack (8WS) Orange | 080926-45131-5 | 45131 | | |
| LiteBox Power Failure System AC/DC chargers & mounting rack (8WF) Orange | 080926-45127-8 | 45127 | | |
| LiteBox Power Failure System AC/DC chargers & mounting rack (8WS) Beige | 080926-45133-9 | 45133 | | |
| LiteBox Power Failure System AC/DC chargers & mounting rack (8WF) Beige | 080926-45129-2 | 45129 | | |
| See reverse side for additional part numbers | | | | |





| Item | | UPC | Part # |
|---|--------|----------------|-----------|
| DC2 direct wire charge cord | | 080926-22050-8 | 22050 |
| DC1 Charge Cord | | 080926-22051-5 | 22051 |
| 120V AC charge cord | | 080926-22311-0 | 22311 |
| Locking Device (keyed differently) **Must be factory installed | | 080926-40163-1 | 40163 |
| Locking Device (keyed alike) **Must be factory installed | | N/A | 40164-525 |
| 8 Watt Spot Lamp Assembly | | 080926-45911-3 | 45911 |
| Quick Release Strap | | 080926-44050-0 | 44050 |
| Shoulder Strap | | 080926-45232-9 | 45232 |
| Standard System Mounting Rack | Orange | 080926-45070-7 | 45070 |
| Direct Wire 12V DC Mounting Rack | Orange | 080926-45071-4 | 45071 |
| Standard System Mounting Rack | Yellow | 080926-45072-1 | 45072 |
| Direct Wire 12V DC Mounting Rack | Yellow | 080926-45074-5 | 45074 |
| Mounting Rack (LiteBox) | Beige | 080926-45073-8 | 45073 |
| 20 Watt Bi-Pin Bulb (100 Hr) | | 080926-45902-1 | 45902 |
| 8 Watt Bi-Pin Bulb (300 Hr) | | 080926-45903-8 | 45903 |
| 8 Watt Flood Lamp Assembly | | 080926-45908-3 | 45908 |
| 20 Watt Flood Lamp Assembly | | 080926-45910-6 | 45910 |
| 8 Watt Spot Lamp Assembly | | 080926-45911-3 | 45911 |
| 20 Watt Spot Lamp Assembly | | 080926-45913-7 | 45913 |
| 8W Dual Filament Lamp Assembly | | 080926-45915-1 | 45915 |
| 8 Watt Dual Filament Bulb | | 080926-45921-2 | 45921 |
| Sealed Lead Acid Battery | | 080926-45937-3 | 45937 |

Examples of one spot and one flood lamp assembly shown for representation

