



Survivor® Division 1 Flashlight

Case Material: Lamp housing, battery housing and battery base are made from high impact super tough nylon, offering exceptional durability and weather resistance. All openings are O ring-sealed. Spring loaded clip with built in attachment ring attaches to belts and harnesses. One way valve for case venting. Available in international safety orange or high visibility yellow.

Dimensions: Height: 6.75 in. (17.15 cm) Height in charger: 8.50 in. (21.6 cm)
 Width: 2.85 in. (7.24 cm) Diameter: 2.87 in. (7.29 cm)

Grip area:

Height: 3.6 in. (9.14 cm) Thickness: 1.35 in. (3.43cm)
 Width: 2.20 in. (5.59 cm)

Weight: 15.4 oz (437 grams)*

Lens: Unbreakable Lexan® Lens with silicone anti-scratch coating is assembled in a heavy duty bezel. O-ring sealed.

Light Source: 2.1-watt xenon bulb with an average life of 30 hours

Light Output: Bulb Rating: Up to 15,000 Peak beam candlepower.
 31 Lumens typical

On/Off: O-ring sealed rotary switch made from flame retardant glass-filled thermoplastic. A ¼" high actuator provides easy operation even when wearing heavy gloves.

Run Time: Operational for up to 4.25 continuous hours between charges

Battery: Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C; can be recharged up to 1,000 times

Charging: AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources. The universal Steady Charger, which requires up to 10 hours for a complete charge, can be used with 110V, 120V, 230V, 240V, or 12V DC by exchanging its charge cord.

- Features:**
- Water resistant
 - Serialized for positive identification

Approvals:** UL Listed for Class I Division 1, Group C, D
 Rack meets requirements of NFPA 1901-12-1.7 mounted in any position.
 Most models meet applicable European Community Directives.

Warranty: "No Excuses" limited lifetime warranty.

*With battery (included in purchase)

** See product for specific ratings.



| Survivor Division 1 Model Part Numbers | | |
|--|--------|-------|
| <i>Steady Charge Model</i> | | |
| Survivor AC/DC w/Charger/Holder | Yellow | 91200 |
| Survivor AC/DC w/Charger/Holder | Orange | 91000 |
| Survivor – (W/out Charger) | Yellow | 91225 |
| Survivor – (W/out Charger) | Orange | 91025 |
| <i>Fast Charge Model</i> | | |
| Survivor w/120 volt AC Fast Charger | Yellow | 91201 |
| Survivor w/120 volt AC Fast Charger | Orange | 91001 |
| Survivor w/12 volt DC Fast Charger | Yellow | 91202 |
| Survivor w/12 volt DC Fast Charger | Orange | 91002 |

| | |
|---|-------|
| Steady Charge (SC) Plug-In Charger Holder | 90010 |
| Steady Charge (SC) PiggyBack Charger | 90110 |
| AC Fast Charger (Includes Holder) | 90011 |
| DC #1 Fast Charger (Includes Holder) | 90012 |
| DC #2 Fast Charger (Includes Holder) | 90013 |
| Bank Charger, (SC) 120 volt AC | 90400 |
| Bank Charger, 12V DC | 90401 |
| 120 volt AC Charge Cord | 22311 |
| 12 volt DC1 Charge Cord | 22051 |
| 12 volt DC2 Direct Wire Charge Cord | 22050 |
| Battery Pack Assembly – Division 1 | 90337 |
| Xenon Bulb – Division 1 | 90320 |
| Facecap Assembly (Division 1 & 2) | 90330 |
| Bezel/Lens Assembly | 90054 |

