

718 VR2

The 718 VR2 is a Positive Pressure Ventilation (PPV) fan that features a 18" cast aluminum airfoil blade and a variable speed electric motor.

The 718 VR2 has solid cushion tires for easy transportation and a step brake that locks both wheels into position. The precision spun steel shroud is adjustable to four angle positions. A steel frame, full roll cage design and heavy gauge steel grill ensure safety and durability of the 718 VR2.

The VR2 provides precise control of air movement and up to 30% more air flow than single speed electric PPVs. Full control of fan speed with the ability to run on GFCI circuits make these units highly versatile.

Specs

Motor	1.25 Variable Speed
HxWxD	21.75" x 22.5" x 20"
Fan Diameter	18"
Weight	85 lbs
Start	2000 watts
Run	1500 watts
RPM	2400
Set Back	6 ft
Angle	18°
CFM	12,355



shown with optional light kit and chevron tape



3842 Redman Dr
Fort Collins, CO 80524

Phone: 800-525-5224
Fax: 970-297-7099

www.supervac.com
info@supervac.com

POSITIVE PRESSURE VENTILATOR

A Super Vac, part number #718VR2, 18” variable speed, electric, positive pressure ventilator shall be supplied. The unit shall be cart style designed with rear mounted wheels, a full height frame, and a tilt-up, full width handle for easy positioning and rapid deployment. All components of the positive pressure ventilator shall 100% manufactured and assembled in the United States.

The pneumatic wheels shall be designed with a “one step” braking system utilizing a single foot operated brake pedal to assure positive engagement to prevent the unit from rolling during operation. The unit shall remain stationary while running at full speed.

The entire frame of the unit shall be constructed of steel that shall surround the shroud and the seven-blade 16” airfoil propeller in a roll cage design that shall enhance lifting and user safety. The blade shall be constructed of precision cast of aluminum alloy #A356. The blade shall be driven by the electric motor engine that shall have a direct drive connection. The blade shall be precision balanced and attached to the engine shaft with a split taper-lock bushing. Any ventilators utilizing belts, pulley, gears, or additional shafts shall not be acceptable.

The shroud and the safety grill shall be designed as to provide maximum air velocity. The positive pressure ventilator shall have a tilt control with four positions including one position that can direct airflow downward. The standard angle of air direction shall be 18 degrees above horizontal ground level and shall be equipped with a lever to set positions of the air flow to 20, 10, 0, and -10 degrees above and below horizontal level.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade. The unit shall be tested to AMCA 240-95 for air movement and the air movement shall exceed 12,355 cubic feet per minute.

The positive pressure ventilator shall be designed with the following:

Motor Manufacturer: Leeson
Horsepower: 1.25 Hp
Rotations per minute: 3600 RPM
Cubic feet per minute: 12,355
Dimensions: 20” deep x 21-3/4” wide x 22-1/2” high
Weight: 85 pounds

The positive pressure ventilator shall have a minimum five (5) year warranty. The motor shall be warranted by the engine manufacturer for a minimum of two (2) years.