BALL INTAKE VALVE Series

LEFT JBIV-LP 5.0"STORZ RIGID X 6.0"F

AZD1ST-NX-F

ALUMINUM / FRONT CRANK / NO PRV

$2585.00 List Price

FEATURES

SPECIFICATIONS

Remote Control	No
Profile	Low Profile
Waterway	5.25 inch (133 mm)
Coupling Size Side A	6" (150mm)
Coupling Size Side B	5" (125 mm)
Weight	26.8
Detent Swivel	No
L D H Inlet	Yes
L D H Outlet	Yes
Pressure Relief Valve	No

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance

A1630-KIT SIDE SHAFT GEARBOX INSTALLATION INSTRUCTIONS (PDF)
BALL VALVE KIT WITH CANBUS MANUAL (PDF)
BIV INSTRUCTION MANUAL (PDF)
LOW PROFILE BALL INTAKE VALVE MANUAL (PDF)
PRESSURE RELIEF VALVE (PDF)
PRESSURE RELIEF VALVE CONFIGURATION WITH GALVANIC ISOLATOR (PDF)
STORZ GASKET REPLACEMENT KIT (PDF)

Technical Specifications and Drawings

AZD1ST-NX-F FINISHED GOOD PRINT - STEP (ZIP)
AZD1ST-NX-F ITEM SPECIFICATION (DOC)

Online Videos

BALL INTAKE VALVE SERIES VIDEO (MP4)

Product Brochures

BALL INTAKE VALVE (BIV) (PDF)
BIV SERIES OVERVIEW (PDF)
GO CONFIGURE (PDF)
MAX FLOW AND OPTIONS BALL INTAKE VALVE (PDF)

Service Procedures

ALUMINUM STORZ LOCK LEVER INSTALLATION (PDF)

© 2021 Task Force Tips. All Rights Reserved.

ABOUT THE BALL INTAKE VALVE SERIES

Constructed of hard anodized and powder coated aluminum alloy, TFT's Ball Intake Valve series has virtually eliminated expensive corrosion related repairs. Available with a choice of manual or remote controls, a fast acting pressure relief valve, and a unique 30 degree swiveling inlet, these valves are the perfect choice for high volume flow operations. The unobstructed, low friction loss water way allows for maximum flow and models even include a low profile version for tight profile pump panels.

Please note: When using the filters to search for a product, Side A refers to the truck side of the valve and Side B refers to the LDH side of the valve.

© 2021 Task Force Tips. All Rights Reserved.