



TWISTER Series

TWISTER TIP 1.0" BSPF

D1040-BD

10&40 GPM DUAL GALLONAGE

\$89.00 List Price

FEATURES

SPECIFICATIONS

Pistol Grip	No
Valve Design	Twist Style Baffle
Flow Rate	10/40gpm (37/150 l/min)
Break Apart Style	Tip Only
Inlet Coupling Style	Knurled
Body Size	1" (25 mm)
Inlet Coupling Swivel	Rigid
Style	Break-Apart
Pressure Mode	Single
Type	Selectable
Operating Pressure	100psi (7bar)
Remote Control	No
Weight	0.6
Bumper Material	Rubber - press fit

DOCUMENTS

Service Procedures

[1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

[1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

[C1024 ITEM SPECIFICATION \(DOC\)](#)

[PARTS LIST: D SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

[PARTS LIST: F SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[Z SPANISH MANUAL: BOQUILLAS TWISTER® AND BUBBLECUP® \(PDF\)](#)

Product Brochures

[SINGLE FLOW TWISTER PRODUCT BROCHURE \(PDF\)](#)

ABOUT THE TWISTER SERIES

The Twister is available as a selectable, dual gallonage, combination nozzle and a fixed flow 95 gpm flow rate. Designed for simplicity and durability, the rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, and high flow fog. The rugged, economical nozzle also accepts the FoamJet multi-expansion foam aspirating attachment.