


QUADRAFOG Series
QUADRAFOG W/GRIP 1.0\"/>
DQS60P

5-10-25-40-60 GPM @ 100 PSI BALL SHUTOFF W/GRIP

\$795.00 List Price
FEATURES

Selectable gallonage nozzle with five flow settings of 5, 10, 24, 40 and 60 gpm @ 100 psi (20-40-90-150-230 l/min @ 7 bar). All lightweight materials, hard coat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Optional color coded pistol grip and handle covers available. Rocker lug 1.0" NH (25mm) swivel is standard.

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	5/10/25/40/60 gpm
Inlet Coupling Style	Rocker
Body Size	1" (25 mm)
Inlet Coupling Swivel	Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Fog Teeth	Fixed
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	3.1
Bumper Material	Rubber - press fit

DOCUMENTS

Service Procedures

[QUADRAFOG SERVICE PROCEDURE \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)
[Z FRENCH MANUEL: THUNDERFOG, QUADRAFOG AND QUADRACUP \(PDF\)](#)

Online Videos

[QUADRAFOG SERIES VIDEO \(MP4\)](#)

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)

Technical Specifications and Drawings

[DQS60P ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[QUADRAFOG 1000 \(QF1000-SL\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)
[QUADRAFOG 150 PN40 EN15182-4 \(PDF\)](#)
ABOUT THE QUADRAFOG SERIES

An excellent selectable gallonage nozzle for any 1" (25mm) or 1.5" (38mm) hose line. The QUADRAFOG is an economical and lightweight combination nozzle suitable for use with low-expansion or multi-expansion foam attachments. 1" versions range are 5-40 gpm (20-150 l/min) or 5-60gpm (20-230 l/min). The 1.5" version has a range of 30-125 gpm (110-470 l/min), and is available in high(100 psi) or low-pressure(75 psi) versions with either a molded rubber bumper or stainless steel spinning fog teeth.